Red Hat Enterprise Linux Release 9.2 Manual Pages on 'ostree-admin-undeploy.1' command

$ man ostree-admin-undeploy.1

OSTREE ADMIN UNDEPLO(1)   ostree admin undeploy   OSTREE ADMIN UNDEPLO(1)

NAME

    ostree-admin-undeploy - Delete deployment at a given index

SYNOPSIS

    ostree admin undeploy {INDEX}

DESCRIPTION

    Deletes the deployment at INDEX. INDEX must be in range and not

    reference the currently booted deployment.

EXAMPLE

    $ ostree admin status

        * gnome-ostree 67e382b11d213a402a5313e61cbc69dfd5ab93cb07.0

           origin refspec: gnome-ostree/buildmain/x86_64-runtime

          gnome-ostree ce19c41036cc45e49b0cecf6b157523c2105c4de1c.0

           origin refspec: gnome-ostree/buildmain/x86_64-runtime

    $ ostree admin undeploy 1

    Transaction complete; bootconfig swap: no deployment count change: -1)

```
    Freed objects: 326.5 kB

    Deleted deployment ce19c41036cc45e49b0cecf6b157523c2105c4de1c.0


$ ostree admin status


    * gnome-ostree 67e382b11d213a402a5313e61cbc69dfd5ab93cb07.0

      origin refspec: gnome-ostree/buildmain/x86_64-runtime
```

OSTree   OSTREE ADMIN UNDEPLO(1)