



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'ostree-admin-upgrade.1' command**

**\$ man ostree-admin-upgrade.1**

OSTREE ADMIN UPGRADE(1) ostree admin upgrade OSTREE ADMIN UPGRADE(1)

### NAME

ostree-admin-upgrade - Construct new tree from current origin and deploy it, if it changed

### SYNOPSIS

ostree admin upgrade [OPTIONS...]

### DESCRIPTION

Downloads the latest version of the current ref from the build server and deploys it, if it changed. Reboot the machine for the changes to take effect. These phases can be split via `--pull-only` and `--deploy-only`.

### OPTIONS

`--os="STATEROOT"`

Use a different operating system root than the current one.

`--pull-only`

Only perform a pull into the repository; do not create a deployment. This option can hence safely be used in a background scheduled job with the assurance of not changing system state.

`--deploy-only`

Create a new deployment from the latest commit in the tracked origin refspec. This option is intended to be used by a scheduled system that detected changes via `--pull-only`, and is ready to deploy them.

`--stage`

Perform deployment finalization at shutdown time. Recommended, and will likely become the default in the future.

`--reboot,-r`

Reboot after a successful upgrade.

`--allow-downgrade`

Permit deployment of chronologically older trees.

`--override-commit="CHECKSUM"`

Deploy CHECKSUM instead of the latest tree.

#### EXAMPLE

```
$ ostree admin upgrade
```

```
No update available.
```

OSTree

OSTREE ADMIN UPGRADE(1)