



## ***Red Hat Enterprise Linux Release 9.2 Manual Pages on 'pam\_succeed\_if.8' command***

***\$ man pam\_succeed\_if.8***

PAM\_SUCCEED\_IF(8)            Linux-PAM            PAM\_SUCCEED\_IF(8)

### NAME

pam\_succeed\_if - test account characteristics

### SYNOPSIS

pam\_succeed\_if.so [flag...] [condition...]

### DESCRIPTION

pam\_succeed\_if.so is designed to succeed or fail authentication based on characteristics of the account belonging to the user being authenticated or values of other PAM items. One use is to select whether to load other modules based on this test.

The module should be given one or more conditions as module arguments, and authentication will succeed only if all of the conditions are met.

### OPTIONS

The following flags are supported:

debug

Turns on debugging messages sent to syslog.

use\_uid

Evaluate conditions using the account of the user whose UID the application is running under instead of the user being authenticated.

quiet

Don't log failure or success to the system log.

quiet\_fail

Don't log failure to the system log.

quiet\_success

Don't log success to the system log.

audit

Log unknown users to the system log.

Conditions are three words: a field, a test, and a value to test for.

Available fields are user, uid, gid, shell, home, ruser, rhost, tty and service:

field < number

Field has a value numerically less than number.

field <= number

Field has a value numerically less than or equal to number.

field eq number

Field has a value numerically equal to number.

field >= number

Field has a value numerically greater than or equal to number.

field > number

Field has a value numerically greater than number.

field ne number

Field has a value numerically different from number.

field = string

Field exactly matches the given string.

field != string

Field does not match the given string.

field =~ glob

Field matches the given glob.

field !~ glob

Field does not match the given glob.

field in item:item:...

Field is contained in the list of items separated by colons.

field notin item:item:...

Field is not contained in the list of items separated by colons.

user ingroup group[:group:....]

User is in given group(s).

user notingroup group[:group:....]

User is not in given group(s).

user inetgr netgroup

(user,host) is in given netgroup.

user notinnetgr group

(user,host) is not in given netgroup.

## MODULE TYPES PROVIDED

All module types (account, auth, password and session) are provided.

## RETURN VALUES

### PAM\_SUCCESS

The condition was true.

### PAM\_AUTH\_ERR

The condition was false.

### PAM\_SERVICE\_ERR

A service error occurred or the arguments can't be parsed correctly.

## EXAMPLES

To emulate the behaviour of pam\_wheel, except there is no fallback to group 0 being only approximated by checking also the root group membership:

```
auth required pam_succeed_if.so quiet user ingroup wheel:root
```

Given that the type matches, only loads the othermodule rule if the UID is over 500. Adjust the number after default to skip several rules.

```
type [default=1 success=ignore] pam_succeed_if.so quiet uid > 500  
type required othermodule.so arguments...
```

## SEE ALSO

glob(7), pam(8)

AUTHOR

Nalin Dahyabhai <nalin@redhat.com>

Linux-PAM

11/25/2020

PAM\_SUCCEED\_IF(8)