



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## ***Red Hat Enterprise Linux Release 9.2 Manual Pages on 'pdfdetach.1' command***

### ***\$ man pdfdetach.1***

pdfdetach(1)            General Commands Manual            pdfdetach(1)

#### NAME

pdfdetach - Portable Document Format (PDF) document embedded file extractor (version 3.03)

#### SYNOPSIS

pdfdetach [options] [PDF-file]

#### DESCRIPTION

Pdfdetach lists or extracts embedded files (attachments) from a Portable Document Format (PDF) file.

#### OPTIONS

Some of the following options can be set with configuration file commands. These are listed in square brackets with the description of the corresponding command line option.

-list List all of the embedded files in the PDF file. File names are converted to the text encoding specified by the "-enc" switch.

-save number

Save the specified embedded file. By default, this uses the file name associated with the embedded file (as printed by the "-list" switch); the file name can be changed with the "-o" switch.

-savefile filename

Save the specified embedded file. By default, this uses the file name associated with the embedded file (as printed by the

"-list" switch); the file name can be changed with the "-o" switch.

#### -saveall

Save all of the embedded files. This uses the file names associated with the embedded files (as printed by the "-list" switch). By default, the files are saved in the current directory; this can be changed with the "-o" switch.

#### -o path

Set the file name used when saving an embedded file with the "-save" switch, or the directory used by "-saveall".

#### -enc encoding-name

Sets the encoding to use for text output (embedded file names). This defaults to "UTF-8".

#### -opw password

Specify the owner password for the PDF file. Providing this will bypass all security restrictions.

#### -upw password

Specify the user password for the PDF file.

-v Print copyright and version information.

-h Print usage information. (-help and --help are equivalent.)

## EXIT CODES

The Xpdf tools use the following exit codes:

- 0 No error.
- 1 Error opening a PDF file.
- 2 Error opening an output file.
- 3 Error related to PDF permissions.
- 99 Other error.

## AUTHOR

The pdftools software and documentation are copyright 1996-2011 Glyph & Cog, LLC.

## SEE ALSO

pdffonts(1), pdfimages(1), pdftools(1), pdftocairo(1), pdftohtml(1), pdftoppm(1), pdftops(1), pdftotext(1), pdfseparate(1), pdfsig(1), pdfu?

nite(1)

15 August 2011

pdfdetach(1)