



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## ***Red Hat Enterprise Linux Release 9.2 Manual Pages on 'pkg-config.1' command***

***\$ man pkg-config.1***

PKGCONF(1) BSD General Commands Manual PKGCONF(1)

### NAME

pkgconf ? a system for configuring build dependency information

### SYNOPSIS

pkgconf [options] [list of modules]

### DESCRIPTION

pkgconf is a program which helps to configure compiler and linker flags for development libraries. This allows build systems to detect other dependencies and use them with the system toolchain.

### GENERAL OPTIONS

--version

Display the supported pkg-config version and exit.

--atleast-pkgconfig-version=VERSION

Exit with error if we do not support the requested pkg-config version.

--errors-to-stdout

Print all errors on the main output stream instead of the error output stream.

--silence-errors

Do not display any errors at all.

--list-all

Walk all directories listed in the PKG\_CONFIG\_PATH environmental variable and display information on packages which have regis?

tered information there.

--simulate

Simulates resolving a dependency graph based on the requested modules on the command line. Dumps a series of trees denoting pkgconf's resolver state.

--no-cache

Skip caching packages when they are loaded into the internal resolver. This may result in an alternate dependency graph being computed.

--ignore-conflicts

Ignore ?Conflicts? rules in modules.

--env-only

Learn about pkgconf's configuration strictly from environmental variables.

--maximum-traverse-depth=DEPTH

Impose a limit on the allowed depth in the dependency graph. For example, a depth of 2 will restrict the resolver from acting on child dependencies of modules added to the resolver's solution.

--static

Compute a deeper dependency graph and use compiler/linker flags intended for static linking.

--shared

Compute a simple dependency graph that is only suitable for shared linking.

--pure Treats the computed dependency graph as if it were pure. This is mainly intended for use with the --static flag.

--no-provides

Ignore ?Provides? rules in modules when resolving dependencies.

--with-path=PATH

Adds a new module search path to pkgconf's dependency resolver. Paths added in this way are given preference before other paths.

--define-prefix

Attempts to determine the prefix variable to use for CFLAGS and

LIBS entry relocations. This is mainly useful for platforms where framework SDKs are relocatable, such as Windows.

`--dont-define-prefix`

Disables the `?define-prefix?` feature.

`--prefix-variable=VARIABLE`

Sets the `?prefix?` variable used by the `?define-prefix?` feature.

`--relocate=PATH`

Relocates a path using the `pkgconf_path_relocate` API. This is mainly used by the testsuite to provide a guaranteed interface to the system's path relocation backend.

`--dont-relocate-paths`

Disables the path relocation feature.

## MODULE-SPECIFIC OPTIONS

`--atleast-version=VERSION`

Exit with error if a module's version is less than the specified version.

`--exact-version=VERSION`

Exit with error if a module's version is not exactly the specified version.

`--max-version=VERSION`

Exit with error if a module's version is greater than the specified version.

`--exists`

Exit with a non-zero result if the dependency resolver was unable to find all of the requested modules.

`--uninstalled`

Exit with a non-zero result if the dependency resolver uses an `?uninstalled?` module as part of its solution.

`--no-uninstalled`

Forbids the dependency resolver from considering 'uninstalled' modules as part of a solution.

## QUERY-SPECIFIC OPTIONS

`--cflags`, `--cflags-only-l`, `--cflags-only-other`

Display either all CFLAGS, only -I CFLAGS or only CFLAGS that are not -I.

--libs, --libs-only-L, --libs-only-I, --libs-only-other

Display either all linker flags, only -L linker flags, only -I linker flags or only linker flags that are not -L or -I.

--keep-system-cflags, --keep-system-libs

Keep CFLAGS or linker flag fragments that would be filtered due to being included by default in the compiler.

--define-variable=VARNAME=VALUE

Define VARNAME as VALUE. Variables are used in query output, and some modules' results may change based on the presence of a variable definition.

--print-variables

Print all seen variables for a module to the output channel.

--print-provides

Print all relevant ?Provides? entries for a module to the output channel.

--variable=VARNAME

Print the value of VARNAME.

--print-requires, --print-requires-private

Print the modules included in either the Requires field or the Requires.private field.

--digraph

Dump the dependency resolver's solution as a graphviz ?dot? file. This can be used with graphviz to visualize module interdependencies.

--path Display the filenames of the ?.pc? files used by the dependency resolver for a given dependency set.

--env=VARNAME

Print the requested values as variable declarations in a similar format as the env(1) command.

--fragment-filter=TYPES

Filter the fragment lists for the specified types.

--modversion

Print the version of the queried module.

## ENVIRONMENT

PKG\_CONFIG\_PATH

List of secondary directories where `?.pc?` files are looked up.

PKG\_CONFIG\_LIBDIR

List of primary directories where `?.pc?` files are looked up.

PKG\_CONFIG\_SYSROOT\_DIR

`?sysroot?` directory, will be prepended to every path defined in `PKG_CONFIG_PATH`. Useful for cross compilation.

PKG\_CONFIG\_TOP\_BUILD\_DIR

Provides an alternative setting for the `?pc_top_builddir?` global variable.

PKG\_CONFIG\_PURE\_DEPGRAPH

If set, enables the same behaviour as the `--pure` flag.

PKG\_CONFIG\_SYSTEM\_INCLUDE\_PATH

List of paths that are considered system include paths by the toolchain. This is a `pkgconf`-specific extension.

PKG\_CONFIG\_SYSTEM\_LIBRARY\_PATH

List of paths that are considered system library paths by the toolchain. This is a `pkgconf`-specific extension.

PKG\_CONFIG\_DISABLE\_UNINSTALLED

If set, enables the same behaviour as the `--no-uninstalled` flag.

PKG\_CONFIG\_LOG

`?logfile?` which is used for dumping audit information concerning installed module versions.

PKG\_CONFIG\_DEBUG\_SPEW

If set, enables additional debug logging. The format of the debug log messages is implementation-specific.

PKG\_CONFIG\_DONT\_RELOCATE\_PATHS

If set, disables the path relocation feature.

PKG\_CONFIG\_MSVC\_SYNTAX

If set, uses MSVC syntax for fragments.

## EXAMPLES

Displaying the CFLAGS of a package:

```
$ pkgconf --cflags foo
```

```
-fPIC -I/usr/include/foo
```

## SEE ALSO

pc(5), pkg.m4(7)

BSD

November 15, 2016

BSD