



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'podman-image-diff.1' command

\$ man podman-image-diff.1

podman-image-diff(1) General Commands Manual podman-image-diff(1)

NAME

podman-image-diff - Inspect changes on an image's filesystem

SYNOPSIS

podman image diff [options] image [image]

DESCRIPTION

Displays changes on an image's filesystem. The image will be compared to its parent layer or the second argument when given.

The output is prefixed with the following symbols:

??

?Symbol ? Description ?

??

?A ? A file or directory was added. ?

??

?D ? A file or directory was ?

? ? deleted. ?

??

?C ? A file or directory was ?

? ? changed. ?

??

OPTIONS

--format

Alter the output into a different format. The only valid format for

podman image diff is json.

EXAMPLE

```
$ podman diff redis:old
C /usr
C /usr/local
C /usr/local/bin
A /usr/local/bin/docker-entrypoint.sh
$ podman diff --format json redis:old redis:alpine
{
  "changed": [
    "/usr",
    "/usr/local",
    "/usr/local/bin"
  ],
  "added": [
    "/usr/local/bin/docker-entrypoint.sh"
  ]
}
```

SEE ALSO

podman(1), podman-image(1)

HISTORY

August 2017, Originally compiled by Ryan Cole rycole@redhat.com
?mailto:rycole@redhat.com?

podman-image-diff(1)