Red Hat Enterprise Linux Release 9.2 Manual Pages on 'podman-image-rm.1' command

$ man podman-image-rm.1

podman-rmi(1)   General Commands Manual   podman-rmi(1)

NAME

    podman-rmi - Removes one or more locally stored images

SYNOPSIS

    podman rmi [options] image [...]

    podman image rm [options] image [...]

DESCRIPTION

    Removes one or more locally stored images. Passing an argument image

    deletes it, along with any of its dangling parent images.   A dangling

    image is an image without a tag and without being referenced by another

    image.

    Note: To delete an image from a remote registry, use the skopeo delete

    command. Some registries do not allow users to delete an image via a

    CLI remotely.

OPTIONS

  --all, -a

    Remove all images in the local storage.

  --force, -f

    This option will cause podman to remove all containers that are using

    the image before removing the image from the system.

  --ignore, -i

    If a specified image does not exist in the local storage, ignore it and

    do not throw an error.

--no-prune

This options will not remove dangling parents of specified image

Remove an image by its short ID

$ podman rmi c0ed59d05ff7

Remove an image and its associated containers.

$ podman rmi --force imageID

Remove multiple images by their shortened IDs.

$ podman rmi c4dfb1609ee2 93fd78260bd1 c0ed59d05ff7

Remove all images and containers.

$ podman rmi -a -f

Remove an absent image with and without the --ignore flag.

$ podman rmi --ignore nothing

$ podman rmi nothing

Error: nothing: image not known

Exit Status

0   All specified images removed

1   One of the specified images did not exist, and no other failures

2   One of the specified images has child images or is being used by a

container

125 The command fails for any other reason

SEE ALSO

podman(1), skopeo-delete(1)

HISTORY

March 2017, Originally compiled by Dan Walsh dwalsh@redhat.com

?mailto:dwalsh@redhat.com?

podman-rmi(1)