

Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'podman-logout.1' command

\$ man podman-logout.1

podman-logout(1)

General Commands Manual

podman-logout(1)

NAME

podman-logout - Logout of a container registry

SYNOPSIS

podman logout [options] registry

DESCRIPTION

podman logout logs out of a specified registry server by deleting the cached credentials stored in the auth.json file. If the registry is not specified, the first registry under [registries.search] from reg? istries.conf will be used. The path of the authentication file can be overridden by the user by setting the authfile flag. The default path used is \${XDG_RUNTIME_DIR}/containers/auth.json. For more details about format and configurations of the auth,json file, please refer to con? tainers-auth.json(5) All the cached credentials can be removed by set? ting the all flag.

podman [GLOBAL OPTIONS]

podman logout [GLOBAL OPTIONS]

OPTIONS

--all, -a

Remove the cached credentials for all registries in the auth file

--authfile=path

ers/auth.json, which is set using podman login. If the authorization state is not found there, \$HOME/.docker/config.json is checked, which is set using docker login.

Note: There is also the option to override the default path of the au? thentication file by setting the REGISTRY_AUTH_FILE environment vari? able. This can be done with export REGISTRY_AUTH_FILE=path.

--help, -h

Print usage statement

EXAMPLES

\$ podman logout docker.io

Remove login credentials for https://registry-1.docker.io/v2/

\$ podman logout --authfile authdir/myauths.json docker.io

Remove login credentials for https://registry-1.docker.io/v2/

\$ podman logout --all

Remove login credentials for all registries

SEE ALSO

podman(1), podman-login(1), containers-auth.json(5)

HISTORY

August 2017, Originally compiled by Urvashi Mohnani umohnani@redhat.com?

?mailto:umohnani@redhat.com?

podman-logout(1)