



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'podman-system-events.1' command

\$ man podman-system-events.1

podman-events(1) General Commands Manual podman-events(1)

NAME

podman-events - Monitor Podman events

SYNOPSIS

podman events [options]

podman system events [options]

DESCRIPTION

Monitor and print events that occur in Podman. Each event will include a timestamp, a type, a status, name (if applicable), and image (if applicable). The default logging mechanism is journald. This can be changed in containers.conf by changing the events_logger value to file. Only file and journald are accepted. A none logger is also available but this logging mechanism completely disables events; nothing will be reported by podman events.

By default, streaming mode is used, printing new events as they occur.

Previous events can be listed via --since and --until.

The container event type will report the follow statuses:

- * attach
- * checkpoint
- * cleanup
- * commit
- * connect
- * create

- * died
- * disconnect
- * exec
- * exec_died
- * exited
- * export
- * import
- * init
- * kill
- * mount
- * pause
- * prune
- * remove
- * rename
- * restart
- * restore
- * start
- * stop
- * sync
- * unmount
- * unpause

The pod event type will report the follow statuses:

- * create
- * kill
- * pause
- * remove
- * start
- * stop
- * unpause

The image event type will report the following statuses:

- * loadFromArchive,
- * mount
- * pull

- * push
- * remove
- * save
- * tag
- * unmount
- * untag

The system type will report the following statuses:

- * refresh
- * renumber

The volume type will report the following statuses:

- * create
- * prune
- * remove

Verbose Create Events

Setting `events_container_create_inspect_data=true` in `containers.conf(5)` instructs Podman to create more verbose container-create events which include a JSON payload with detailed information about the containers.

The JSON payload is identical to the one of `podman-container-inspect(1)`. The associated field in journald is named `PODMAN_CONTAINER_INSPECT_DATA`.

OPTIONS

`--filter, -f=filter`

Filter events that are displayed. They must be in the format of "filter=value". The following filters are supported:

- * container=name_or_id
- * event=event_status (described above)
- * image=name_or_id
- * label=key=value
- * pod=name_or_id
- * volume=name_or_id
- * type=event_type (described above)

In the case where an ID is used, the ID may be in its full or shortened form. The "die" event is mapped to "died" for Docker compatibility.

--format

Format the output to JSON Lines or using the given Go template.

??

?Placeholder ? Description ?

??

?.Attributes ? created_at, _by, labels, and ?

? ? more (map[]) ?

??

?.ContainerExitCode ? Exit code (int) ?

??

?.Details ... ? Internal structure, not actu? ?

? ? ally useful ?

??

?.HealthStatus ? Health Status (string) ?

??

?.ID ? Container ID (full 64-bit SHA) ?

??

?.Image ? Name of image being run ?

? ? (string) ?

??

?.Name ? Container name (string) ?

??

?.Network ? Name of network being used ?

? ? (string) ?

??

?.Status ? Event status (e.g., create, ?

? ? start, died, ...) ?

??

?.Time ? Event timestamp (string) ?

??

?.Type ? Event type (e.g., image, con? ?

? ? tainer, pod, ...) ?

??


```
$ podman events --filter event=create --filter type=pod
```

```
2019-03-02 10:44:29.601746633 -0600 CST pod create 1df5ebca7b44 (image=, name=confident_hawking)
```

```
2019-03-02 10:44:42.374637304 -0600 CST pod create ca731231718e (image=, name=webapp)
```

```
2019-03-02 10:44:47.486759133 -0600 CST pod create 71e807fc3a8e (image=, name=reverent_swanson)
```

Show only Podman events created in the last five minutes:

```
$ sudo podman events --since 5m
```

```
2019-03-02 10:44:29.598835409 -0600 CST container create b629d10d3831 (image=k8s.gcr.io/pause:3.1,
name=1df5ebca7b44-infra)
```

```
2019-03-02 10:44:29.601746633 -0600 CST pod create 1df5ebca7b44 (image=, name=confident_hawking)
```

```
2019-03-02 10:44:42.371100253 -0600 CST container create 170a0f457d00 (image=k8s.gcr.io/pause:3.1,
name=ca731231718e-infra)
```

```
2019-03-02 10:44:42.374637304 -0600 CST pod create ca731231718e (image=, name=webapp)
```

Show Podman events in JSON Lines format

```
$ podman events --format json
```

```
{"ID":"683b0909d556a9c02fa8cd2b61c3531a965db42158627622d1a67b391964d519","Image":"localhost/myshdemo:latest",
,"Name":"agitated_diffie","Status":"cleanup","Time":"2019-04-27T22:47:00.849932843-04:00","Type":"container"}
```

```
{"ID":"a0f8ab051bfd43f9c5141a8a2502139707e4b38d98ac0872e57c5315381e88ad","Image":"docker.io/library/alpine:latest",
,"Name":"friendly_tereshkova","Status":"unmount","Time":"2019-04-28T13:43:38.063017276-04:00","Type":"container"}
```

SEE ALSO

podman(1), containers.conf(5)

HISTORY

March 2019, Originally compiled by Brent Baude bbaude@redhat.com

[?mailto:bbaude@redhat.com?](mailto:bbaude@redhat.com)

podman-events(1)