



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'podman-unpause.1' command

\$ man podman-unpause.1

podman-unpause(1) General Commands Manual podman-unpause(1)

NAME

podman-unpause - Unpause one or more containers

SYNOPSIS

podman unpause [options][[container ...]

podman container unpause [options][[container ...]

DESCRIPTION

Unpauses the processes in one or more containers. Container IDs or names can be used as input.

OPTIONS

--all, -a

Unpause all paused containers.

--cidfile=file

Read container ID from the specified file and unpause the container.

Can be specified multiple times.

--filter, -f=filter

Filter what containers unpause. Multiple filters can be given with multiple uses of the --filter flag. Filters with the same key work inclusive with the only exception being label which is exclusive. Filters with different keys always work exclusive.

Valid filters are listed below:

??

?Filter ? Description ?

??

?id ? [ID] Container's ID (accepts ?

? ? regex) ?

??

?name ? [Name] Container's name (ac? ?

? ? cepts regex) ?

??

?label ? [Key] or [Key=Value] Label ?

? ? assigned to a container ?

??

?exited ? [Int] Container's exit code ?

??

?status ? [Status] Container's status: ?

? ? 'created', 'exited', ?

? ? 'paused', 'running', 'un? ?

? ? known' ?

??

?ancestor ? [ImageName] Image or descen? ?

? ? dant used to create container ?

??

?before ? [ID] or [Name] Containers ?

? ? created before this container ?

??

?since ? [ID] or [Name] Containers ?

? ? created since this container ?

??

?volume ? [VolumeName] or [Mountpoint? ?

? ? Destination] Volume mounted ?

? ? in container ?

??

?health ? [Status] healthy or unhealthy ?

??

?pod ? [Pod] name or full or partial ?

? ? ID of pod ?
??
?network ? [Network] name or full ID of ?
? ? network ?
??

--latest, -l

Instead of providing the container name or ID, use the last created container. Note: the last started container could be from other users of Podman on the host machine. (This option is not available with the remote Podman client, including Mac and Windows (excluding WSL2) machines)

EXAMPLE

Unpause container called 'mywebserver'

```
podman unpause mywebserver
```

Unpause container by a partial container ID.

```
podman unpause 860a4b23
```

Unpause all paused containers.

```
podman unpause --all
```

Unpause container using ID specified in a given files.

```
podman unpause --cidfile /home/user/cidfile-1  
podman unpause --cidfile /home/user/cidfile-1 --cidfile ./cidfile-2
```

Unpause the latest container created by Podman.

```
podman unpause --latest
```

SEE ALSO

podman(1), podman-pause(1)

HISTORY

September 2017, Originally compiled by Dan Walsh dwalsh@redhat.com
[?mailto:dwalsh@redhat.com?](mailto:dwalsh@redhat.com)

podman-unpause(1)