



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'pthread_attr_getstack.3' command

\$ man pthread_attr_getstack.3

PTHREAD_ATTR_SETSTACK(3) Linux Programmer's Manual PTHREAD_ATTR_SETSTACK(3)

NAME

pthread_attr_setstack, pthread_attr_getstack - set/get stack attributes
in thread attributes object

SYNOPSIS

```
#include <pthread.h>

int pthread_attr_setstack(pthread_attr_t *attr,
                          void *stackaddr, size_t stacksize);

int pthread_attr_getstack(const pthread_attr_t *attr,
                          void **stackaddr, size_t *stacksize);
```

Compile and link with `-pthread`.

Feature Test Macro Requirements for glibc (see `feature_test_macros(7)`):

```
pthread_attr_getstack(), pthread_attr_setstack():
    _POSIX_C_SOURCE >= 200112L
```

DESCRIPTION

The `pthread_attr_setstack()` function sets the stack address and stack size attributes of the thread attributes object referred to by `attr` to the values specified in `stackaddr` and `stacksize`, respectively. These attributes specify the location and size of the stack that should be used by a thread that is created using the thread attributes object `attr`.

`stackaddr` should point to the lowest addressable byte of a buffer of `stacksize` bytes that was allocated by the caller. The pages of the al?

located buffer should be both readable and writable.

The pthread_attr_getstack() function returns the stack address and stack size attributes of the thread attributes object referred to by attr in the buffers pointed to by stackaddr and stacksize, respectively.

RETURN VALUE

On success, these functions return 0; on error, they return a nonzero error number.

ERRORS

pthread_attr_setstack() can fail with the following error:

EINVAL stacksize is less than PTHREAD_STACK_MIN (16384) bytes. On some systems, this error may also occur if stackaddr or stackaddr + stacksize is not suitably aligned.

POSIX.1 also documents an EACCES error if the stack area described by stackaddr and stacksize is not both readable and writable by the caller.

VERSIONS

These functions are provided by glibc since version 2.2.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?pthread_attr_setstack(), ? Thread safety ? MT-Safe ?

?pthread_attr_getstack() ? ? ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008.

NOTES

These functions are provided for applications that must ensure that a thread's stack is placed in a particular location. For most applications, this is not necessary, and the use of these functions should be

avoided. (Use `pthread_attr_setstacksize(3)` if an application simply requires a stack size other than the default.)

When an application employs `pthread_attr_setstack()`, it takes over the responsibility of allocating the stack. Any guard size value that was set using `pthread_attr_setguardsize(3)` is ignored. If deemed necessary, it is the application's responsibility to allocate a guard area (one or more pages protected against reading and writing) to handle the possibility of stack overflow.

The address specified in `stackaddr` should be suitably aligned: for full portability, align it on a page boundary (`sysconf(_SC_PAGESIZE)`). `posix_memalign(3)` may be useful for allocation. Probably, `stacksize` should also be a multiple of the system page size.

If `attr` is used to create multiple threads, then the caller must change the stack address attribute between calls to `pthread_create(3)`; otherwise, the threads will attempt to use the same memory area for their stacks, and chaos will ensue.

EXAMPLES

See `pthread_attr_init(3)`.

SEE ALSO

`mmap(2)`, `mprotect(2)`, `posix_memalign(3)`, `pthread_attr_init(3)`,
`pthread_attr_setguardsize(3)`, `pthread_attr_setstackaddr(3)`,
`pthread_attr_setstacksize(3)`, `pthread_create(3)`, `pthreads(7)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at

<https://www.kernel.org/doc/man-pages/>.