



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'pw-jack.1' command

\$ man pw-jack.1

PW-JACK(1) General Commands Manual PW-JACK(1)

NAME

pw-jack - Use PipeWire instead of JACK

SYNOPSIS

pw-jack [options] COMMAND [FILE]

DESCRIPTION

pw-jack modifies the LD_LIBRARY_PATH environment variable so that applications will load PipeWire's reimplementation of the JACK client libraries instead of JACK's own libraries. This results in JACK clients being redirected to PipeWire.

If PipeWire's reimplementation of the JACK client libraries has been installed as a system-wide replacement for JACK's own libraries, then the whole system already behaves in that way, in which case pw-jack has no practical effect.

OPTIONS

- h Show help.
- r NAME
The name of the remote instance to connect to. If left unspecified, a connection is made to the default PipeWire instance.
- v Verbose operation.

EXAMPLES

pw-jack sndfile-jackplay /usr/share/sounds/freedesktop/stereo/bell.oga

NOTES

Using PipeWire for audio is currently considered to be experimental.

AUTHORS

The PipeWire Developers <?

<https://gitlab.freedesktop.org/pipewire/pipewire/issues>; PipeWire is

available from <https://pipewire.org>

SEE ALSO

[pipewire\(1\)](#), [jackd\(1\)](#),

[PW-JACK\(1\)](#)