



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'rand.3' command

\$ man rand.3

RAND(3) Linux Programmer's Manual RAND(3)

NAME

rand, rand_r, srand - pseudo-random number generator

SYNOPSIS

```
#include <stdlib.h>
```

```
int rand(void);
```

```
int rand_r(unsigned int *seedp);
```

```
void srand(unsigned int seed);
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

rand_r():

Since glibc 2.24:

```
_POSIX_C_SOURCE >= 199506L
```

Glibc 2.23 and earlier

```
_POSIX_C_SOURCE
```

DESCRIPTION

The rand() function returns a pseudo-random integer in the range 0 to RAND_MAX inclusive (i.e., the mathematical range [0, RAND_MAX]).

The srand() function sets its argument as the seed for a new sequence of pseudo-random integers to be returned by rand(). These sequences are repeatable by calling srand() with the same seed value.

If no seed value is provided, the rand() function is automatically seeded with a value of 1.

The function rand() is not reentrant, since it uses hidden state that

is modified on each call. This might just be the seed value to be used by the next call, or it might be something more elaborate. In order to get reproducible behavior in a threaded application, this state must be made explicit; this can be done using the reentrant function `rand_r()`. Like `rand()`, `rand_r()` returns a pseudo-random integer in the range `[0, RAND_MAX]`. The `seedp` argument is a pointer to an unsigned int that is used to store state between calls. If `rand_r()` is called with the same initial value for the integer pointed to by `seedp`, and that value is not modified between calls, then the same pseudo-random sequence will result.

The value pointed to by the `seedp` argument of `rand_r()` provides only a very small amount of state, so this function will be a weak pseudo-random generator. Try `drand48_r(3)` instead.

RETURN VALUE

The `rand()` and `rand_r()` functions return a value between 0 and `RAND_MAX` (inclusive). The `srand()` function returns no value.

ATTRIBUTES

For an explanation of the terms used in this section, see [attributes\(7\)](#).

??
?Interface ? Attribute ? Value ?
??
?rand(), rand_r(), srand() ? Thread safety ? MT-Safe ?
??

CONFORMING TO

The functions `rand()` and `srand()` conform to SVr4, 4.3BSD, C89, C99, POSIX.1-2001. The function `rand_r()` is from POSIX.1-2001. POSIX.1-2008 marks `rand_r()` as obsolete.

NOTES

The versions of `rand()` and `srand()` in the Linux C Library use the same random number generator as `random(3)` and `srandom(3)`, so the lower-order bits should be as random as the higher-order bits. However, on older `rand()` implementations, and on current implementations on different

systems, the lower-order bits are much less random than the higher-order bits. Do not use this function in applications intended to be portable when good randomness is needed. (Use `random(3)` instead.)

EXAMPLES

POSIX.1-2001 gives the following example of an implementation of `rand()` and `srand()`, possibly useful when one needs the same sequence on two different machines.

```
static unsigned long next = 1;

/* RAND_MAX assumed to be 32767 */
int myrand(void) {
    next = next * 1103515245 + 12345;
    return((unsigned)(next/65536) % 32768);
}

void mysrand(unsigned int seed) {
    next = seed;
}
```

The following program can be used to display the pseudo-random sequence produced by `rand()` when given a particular seed.

```
#include <stdlib.h>
#include <stdio.h>

int
main(int argc, char *argv[])
{
    int r, nloops;
    unsigned int seed;
    if (argc != 3) {
        fprintf(stderr, "Usage: %s <seed> <nloops>\n", argv[0]);
        exit(EXIT_FAILURE);
    }
    seed = atoi(argv[1]);
    nloops = atoi(argv[2]);
    srand(seed);
    for (int j = 0; j < nloops; j++) {
```

```
    r = rand();
    printf("%d\n", r);
}
exit(EXIT_SUCCESS);
}
```

SEE ALSO

drand48(3), random(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2020-11-01

RAND(3)