



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## ***Red Hat Enterprise Linux Release 9.2 Manual Pages on 'resizecons.8' command***

**\$ man resizecons.8**

RESIZECONS(8)            System Manager's Manual            RESIZECONS(8)

NAME

resizecons - change kernel idea of the console size

SYNOPSIS

resizecons COLSxROWS

resizecons -lines ROWS

DESCRIPTION

The `resizecons` command tries to change the videomode of the console.

There are several aspects to this: (a) the kernel must know about it,

(b) the hardware must know about it, (c) user programs must know about it, (d) the console font may have to be adapted.

(a) The kernel is told about the change using the `ioctl VT_RESIZE`.

This causes the kernel to reallocate console screen memory for all vir?

tual consoles, and might fail if there is not enough memory. (In that case, try to disallocate some virtual consoles first.) If this `ioctl`

succeeds, but a later step fails (e.g., because you do not have root permissions), you may be left with a very messy screen.

The most difficult part of this is (b), since it requires detailed knowledge of the video card hardware, and the setting of numerous `reg?`

isters. Only changing the number of rows is slightly easier, and re?

`sizecons` will try to do that itself, when given the `-lines` option.

(Probably, root permission will be required.) The command `resizecons`

`COLSxROWS` will execute `restoretextmode -r COLSxROWS` (and hence requires

that you have `svgalib` installed). Here `COLSxROWS` is a file that was created earlier by `restoretexmode -w COLSxROWS`. Again, either `root` permissions are required, or `restoretexmode` has to be `suid root`.

In order to deal with (c), `resizecons` does a ``stty rows ROWS cols COLS'` for each active console (in the range `tty0..tty15`), and sends a `SIG? WINCH` signal to selection if it finds the file `/tmp/selection.pid`.

Finally, (d) is dealt with by executing a `setfont` command. Most likely, the wrong font is loaded, and you may want to do another `setfont your? self` afterwards.

## BUGS

`resizecons` does not work on all hardware. This command used to be called `resize`, but was renamed to avoid conflict with another command with the same name.

## SEE ALSO

`setfont(8)`, `stty(1)`, `selection(1)`, `restoretexmode(8)`, `disalloc(8)`

`kbd`

17 Jan 1995

`RESIZECONS(8)`