



Full credit is given to the above companies including the OS that this PDF file was generated!

### Red Hat Enterprise Linux Release 9.2 Manual Pages on 'rewinddir.3' command

**\$ man rewinddir.3**

REWINDDIR(3)          Linux Programmer's Manual          REWINDDIR(3)

#### NAME

rewinddir - reset directory stream

#### SYNOPSIS

```
#include <sys/types.h>
#include <dirent.h>
void rewinddir(DIR *dirp);
```

#### DESCRIPTION

The `rewinddir()` function resets the position of the directory stream `dirp` to the beginning of the directory.

#### RETURN VALUE

The `rewinddir()` function returns no value.

#### ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

??

?Interface ? Attribute ? Value ?

??

?rewinddir() ? Thread safety ? MT-Safe ?

??

#### CONFORMING TO

POSIX.1-2001, POSIX.1-2008, SVr4, 4.3BSD.

#### SEE ALSO

closedir(3), opendir(3), readdir(3), scandir(3), seekdir(3), telldir(3)

## COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2015-08-08

REWINDDIR(3)