



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'rustdoc.1' command

\$ man rustdoc.1

RUSTDOC(1) User Commands RUSTDOC(1)

NAME

rustdoc - generate documentation from Rust source code

SYNOPSIS

rustdoc [OPTIONS] INPUT

DESCRIPTION

This tool generates API reference documentation by extracting comments from source code written in the Rust language, available at <https://www.rust-lang.org>. It accepts several input formats and provides several output formats for the generated documentation.

OPTIONS

-r, --input-format FORMAT

rust

-w, --output-format FORMAT

html

-o, --output OUTPUT,

where to place the output (default: doc/ for html)

--passes LIST

space-separated list of passes to run (default: ")

--no-defaults

don't run the default passes

--plugins LIST

space-separated list of plugins to run (default: ")

`--plugin-path DIR`
directory to load plugins from (default: `/tmp/rustdoc_ng/plugins`)

`--target TRIPLE`
target triple to document

`--crate-name NAME`
specify the name of this crate

`-L, --library-path DIR`
directory to add to crate search path

`--cfg SPEC`
pass a `--cfg` to rustc

`--extern VAL`
pass an `--extern` to rustc

`--test` run code examples as tests

`--test-args ARGS`
pass arguments to the test runner

`--html-in-header FILE`
file to add to `<head>`

`--html-before-content FILES`
files to include inline between `<body>` and the content of a rendered Markdown file or generated documentation

`--markdown-before-content FILES`
files to include inline between `<body>` and the content of a rendered Markdown file or generated documentation

`--html-after-content FILES`
files to include inline between the content and `</body>` of a rendered Markdown file or generated documentation

`--markdown-after-content FILES`
files to include inline between the content and `</body>` of a rendered Markdown file or generated documentation

`--markdown-css FILES`
CSS files to include via `<link>` in a rendered Markdown file or generated documentation

--markdown-playground-url URL

URL to send code snippets to

--markdown-no-toc

don't include table of contents

-h, --extend-css

to redefine some css rules with a given file to generate doc

with your own theme

-V, --version

Print rustdoc's version

OUTPUT FORMATS

The rustdoc tool can generate output in an HTML format.

If using an HTML format, then the specified output destination will be

the root directory of an HTML structure for all the documentation.

Pages will be placed into this directory, and source files will also

possibly be rendered into it as well.

EXAMPLES

To generate documentation for the source in the current directory:

```
$ rustdoc hello.rs
```

List all available passes that rustdoc has, along with default passes:

```
$ rustdoc --passes list
```

The generated HTML can be viewed with any standard web browser.

SEE ALSO

rustc(1)

BUGS

See <https://github.com/rust-lang/rust/issues> for issues.

AUTHOR

See the version control history or <https://thanks.rust-lang.org>

COPYRIGHT

This work is dual?licensed under Apache 2.0 and MIT terms. See COPY?

RIGHT file in the rust source distribution.

rustdoc <INSERT VERSION HERE> July 2018

RUSTDOC(1)