Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'sane-ricoh.5' command

$ man sane-ricoh.5

sane-ricoh(5) SANE Scanner Access Now Easy sane-ricoh(5)

NAME

sane-ricoh - SANE backend for Ricoh flatbed scanners

DESCRIPTION

The sane-ricoh library implements a SANE (Scanner Access Now Easy) backend that provides access to the following Ricoh flatbed scanners:

IS50

IS60

DEVICE NAMES

This backend expects device names of the form:

special

Where special is the path-name for the special device that corresponds to a SCSI scanner. The special device name must be a generic SCSI de? vice or a symlink to such a device. The program sane-find-scanner(1) helps to find out the correct device. Under Linux, such a device name could be /dev/sga or /dev/sge, for example. See sane-scsi(5) for de? tails.

FILES

/etc/sane.d/ricoh.conf

The backend configuration file (see also description of SANE_CONFIG_DIR below).

/usr/lib64/sane/libsane-ricoh.a

The static library implementing this backend.

/usr/lib64/sane/libsane-ricoh.so

The shared library implementing this backend (present on systems that support dynamic loading).

ENVIRONMENT

SANE_CONFIG_DIR

This environment variable specifies the list of directories that may contain the configuration file. Under UNIX, the directories are separated by a colon (`:'), under OS/2, they are separated by a semi-colon (`;'). If this variable is not set, the config? uration file is searched in two default directories: first, the current working directory (".") and then in /etc/sane.d. If the value of the environment variable ends with the directory sepa? rator character, then the default directories are searched after the explicitly specified directories. For example, setting SANE_CONFIG_DIR to "/tmp/config:" would result in directories tmp/config, ., and /etc/sane.d being searched (in this order).

SANE_DEBUG_RICOH

If the library was compiled with debug support enabled, this en? vironment variable controls the debug level for this backend. Higher debug levels increase the verbosity of the output.

Example: export SANE_DEBUG_RICOH=4

SEE ALSO

sane(7), sane-scsi(5), sane-find-scanner(1)

AUTHOR

Feico W. Dillema