Red Hat Enterprise Linux Release 9.2 Manual Pages on 'scsi_mandat.8' command

$ man scsi_mandat.8

SCSI_MANDAT(8)   SG3_UTILS   SCSI_MANDAT(8)

NAME

    scsi_mandat - check SCSI device support for mandatory commands

SYNOPSIS

    scsi_mandat [--help] [--log] [--quiet] [--verbose] DEVICE

DESCRIPTION

    This bash shell script calls several SCSI commands on the given DEVICE.

    These SCSI commands are considered mandatory (although that varies a

    little depending on which standard/draft the DEVICE complies with). The

    results of each test and a pass/fail count are output.

OPTIONS

    Arguments to long options are mandatory for short options as well.

    -h, --help

        print out the usage message then exit.

    -L, --log

        the output to stderr (from each SCSI command executed) is ap?

        pended to a file called 'scsi_mandat.err' in the current working

        directory.

    -q, --quiet

        the amount of output is reduced and typically only the pass/fail

        count is output.

    -v, --verbose

        increase level or verbosity.

EXIT STATUS

The exit status of this script is the number of "bad" errors found. So

an exit status of 0 means all mandatory SCSI commands worked as ex‐

pected.

AUTHORS

Written by D. Gilbert

COPYRIGHT

SEE ALSO

sg_inq,sg_luns,sg_turs,sg_requests,sg_vpd,sg_senddiag (sg3_utils)

sg3_utils-1.36   May 2013   SCSI_MANDAT(8)