



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'services.5' command

\$ man services.5

SERVICES(5) Linux Programmer's Manual SERVICES(5)

NAME

services - Internet network services list

DESCRIPTION

services is a plain ASCII file providing a mapping between human-friendly textual names for internet services, and their underlying assigned port numbers and protocol types. Every networking program should look into this file to get the port number (and protocol) for its service. The C library routines getservent(3), getservbyname(3), getservbyport(3), setservent(3), and endservent(3) support querying this file from programs.

Port numbers are assigned by the IANA (Internet Assigned Numbers Authority), and their current policy is to assign both TCP and UDP protocols when assigning a port number. Therefore, most entries will have two entries, even for TCP-only services.

Port numbers below 1024 (so-called "low numbered" ports) can be bound to only by root (see bind(2), tcp(7), and udp(7)). This is so clients connecting to low numbered ports can trust that the service running on the port is the standard implementation, and not a rogue service run by a user of the machine. Well-known port numbers specified by the IANA are normally located in this root-only space.

The presence of an entry for a service in the services file does not necessarily mean that the service is currently running on the machine.

See `inetd.conf(5)` for the configuration of Internet services offered.

Note that not all networking services are started by `inetd(8)`, and so won't appear in `inetd.conf(5)`. In particular, news (NNTP) and mail (SMTP) servers are often initialized from the system boot scripts.

The location of the `services` file is defined by `_PATH_SERVICES` in `<netdb.h>`. This is usually set to `/etc/services`.

Each line describes one service, and is of the form:

```
service-name port/protocol [aliases ...]
```

where:

`service-name`

is the friendly name the service is known by and looked up under. It is case sensitive. Often, the client program is named after the `service-name`.

`port` is the port number (in decimal) to use for this service.

`protocol`

is the type of protocol to be used. This field should match an entry in the `protocols(5)` file. Typical values include `tcp` and `udp`.

`aliases`

is an optional space or tab separated list of other names for this service. Again, the names are case sensitive.

Either spaces or tabs may be used to separate the fields.

Comments are started by the hash sign (`#`) and continue until the end of the line. Blank lines are skipped.

The `service-name` should begin in the first column of the file, since leading spaces are not stripped. `service-names` can be any printable characters excluding space and tab. However, a conservative choice of characters should be used to minimize compatibility problems. For example, `a-z`, `0-9`, and hyphen (`-`) would seem a sensible choice.

Lines not matching this format should not be present in the file.

(Currently, they are silently skipped by `getservent(3)`, `getservbyname(3)`, and `getservbyport(3)`. However, this behavior should not be relied on.)

This file might be distributed over a network using a network-wide naming service like Yellow Pages/NIS or BIND/Hesiod.

A sample services file might look like this:

```
netstat    15/tcp
qotd      17/tcp    quote
msp       18/tcp    # message send protocol
msp       18/udp    # message send protocol
chargen   19/tcp    ttytst source
chargen   19/udp    ttytst source
ftp       21/tcp
# 22 - unassigned
telnet    23/tcp
```

FILES

/etc/services

The Internet network services list

<netdb.h>

Definition of `_PATH_SERVICES`

SEE ALSO

listen(2), endservent(3), getservbyname(3), getservbyport(3), getserverent(3), setservent(3), inetd.conf(5), protocols(5), inetd(8)

Assigned Numbers RFC, most recently RFC 1700, (AKA STD0002).

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux

2020-04-11

SERVICES(5)