



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'seusers.5' command

\$ man seusers.5

seusers(5) SELinux configuration seusers(5)

NAME

seusers - The SELinux GNU/Linux user to SELinux user mapping configuration file

DESCRIPTION

The seusers file contains a list GNU/Linux user to SELinux user mapping for use by SELinux-aware login applications such as PAM(8).

selinux_usersconf_path(3) will return the active policy path to this file. The default SELinux users mapping file is located at:

`/etc/selinux/{SELINUXTYPE}/seusers`

Where {SELINUXTYPE} is the entry from the selinux configuration file config (see selinux_config(5)).

getseuserbyname(3) reads this file to map a GNU/Linux user or group to an SELinux user.

FILE FORMAT

Each line of the seusers configuration file consists of the following:

`[%group_id][user_id]:seuser_id[:range]`

Where:

`group_id|user_id`

The GNU/Linux user id, or if preceded by the percentage (%) symbol, then a GNU/Linux group id.

An optional entry set to `__default__` can be provided as a fall back if required.

`seuser_id`

The SELinux user identity.

`range`

The optional level or range for an MLS/MCS policy.

EXAMPLE

```
# ./seusers
system_u:system_u:s0-s15:c0.c255
root:root:s0-s15:c0.c255
fred:user_u:s0
__default__:user_u:s0
%user_group:user_u:s0
```

SEE ALSO

[selinux\(8\)](#), [PAM\(8\)](#), [selinux_usersconf_path\(3\)](#), [getseuserbyname\(3\)](#),
[selinux_config\(5\)](#)