



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'sg\_unmap.8' command**

**\$ man sg\_unmap.8**

SG\_UNMAP(8)                    SG3\_UTILS                    SG\_UNMAP(8)

### NAME

sg\_unmap - send SCSI UNMAP command (known as 'trim' in ATA specs)

### SYNOPSIS

```
sg_unmap [--all=ST,RN[,LA]] [--anchor] [--dry-run] [--force] [--grp?
num=GN] [--help] [--in=FILE] [--lba=LBA,LBA...] [--num=NUM,NUM...]
[--timeout=TO] [--verbose] [--version] DEVICE
```

### DESCRIPTION

Send a SCSI UNMAP command to DEVICE to unmap one or more logical blocks. This command was introduced in SBC-3 revision 18 under the broad heading of "logical block provisioning". Logical blocks may also be unmapped by the SCSI WRITE SAME command; see the sg\_write\_same utility. The unmap capability is closely related to the ATA DATA SET MANAGEMENT command with the "Trim" bit set.

Logical blocks to be unmapped can be specified in one of three ways to this utility. One way is by supplying the start LBAs to the '--lba=' option and the corresponding number(s) to unmap to the '--num=' option. Another way is by putting start LBA and number to unmap pairs in a file whose name is given to the '--in=' option. Alternatively a large segment or all of a disk (SSD) can be unmapped with the --all=ST\_RN[,LA] option. All values are assumed to be decimal unless prefixed by "0x" (or "0X") or have a trailing "h" (or "H") in which case they are interpreted as hexadecimal. Suffix multipliers are permitted on decimal

values (e.g. '--num=1m').

When the '--lba=' option is given then the '--num=' option must also be given. If one has a comma separated list as its argument then the other must have the same number of elements in its list. The arguments can use a single space as a separator but need to be in quotes or escaped to not be misinterpreted by the shell.

With the '--in=FILE' option an even number of values must be found and are interpreted as pairs: the first value in each pair is a starting LBA and the second value is the number to unmap from that LBA. Everything from and including a "#" on a line is ignored as are blank lines.

Values may be comma, space and tab separated or appear on separate lines. Each line should not exceed 1023 bytes in length.

Since a lot of data can be lost with this utility, a 15 second "cooling off" period is given before any UNMAP commands are sent. During this period the user is reminded what will happen, and to which device, so they can use control-C (or some other technique) to terminate this utility before any unmapping takes place. This period can be bypassed with the --force option.

## OPTIONS

Arguments to long options are mandatory for short options as well.

-A, --all=ST,RN[,LA]

where ST is the starting LBA, RN is the repeat number which is the maximum number of blocks in each SCSI UNMAP command, and LA, if given, is the last LBA to unmap. If LA is not given, then the last LBA on the DEVICE is used. That is obtained by the SCSI READ CAPACITY command.

-a, --anchor

sets the 'Anchor' bit in the command (introduced in sbc3r22).

-d, --dry-run

perform all the preparation, including opening DEVICE plus sending a 'standard' SCSI INQUIRY command (and optionally a READ CAPACITY), but exit before performing any SCSI UNMAP commands.

-f, --force

bypass the 15 second warning period that occurs before any UNMAP commands are sent.

**-g, --grpnum=GN**

sets the 'Group number' field to GN. Defaults to a value of zero. GN should be a value between 0 and 63.

**-h, --help**

output the usage message then exit.

**-l, --in=FILE**

where FILE is a file name containing pairs of values. The first member of each pair is a starting LBA and the second member of the pair is the number of logical blocks to unmap from and including that starting LBA. Values are interpreted as decimal unless indicated otherwise. This option cannot be present with the '--lba=' option.

**-l, --lba=LBA,LBA...**

where LBA,LBA... is a string of comma (or space) separated values that are interpreted as starting logical block addresses. Each number is interpreted as decimal unless prefixed by '0x' or '0X' (or it has a trailing 'h' or 'H'). An argument that contains any space separators needs to be quoted (or otherwise escaped). When this option is given then the '--num=' option must also be given and they must contain the same number of elements in their arguments.

**-n, --num=NUM,NUM...**

where NUM,NUM... is a string of comma (or space) separated values that are interpreted as a number of logical blocks to unmap. Each number is interpreted as decimal unless prefixed by '0x' or '0X' (or it has a trailing 'h' or 'H'). Note that 0 blocks is acceptable. An argument that contains any space separators needs to be quoted (or otherwise escaped). When this option is given then the '--lba=' option must also be given and they must contain the same number of elements in their arguments.

**-t, --timeout=TO**

where TO is a timeout value (in seconds) for the UNMAP command.

The default value is 60 seconds.

-v, --verbose

increase the level of verbosity, (i.e. debug output).

-V, --version

print the version string and then exit.

## NOTES

Some limits: an LBA can be up to 64 bits, a NUM up to 32 bits (imposed by structure of UNMAP SCSI command parameter data). The NUM is further constrained by the MAXIMUM UNMAP LBA COUNT field in the BLOCK LIMITS VPD page (0xb0). The maximum number of LBA,NUM pairs is limited to 128 by this utility and may be further constrained by the MAXIMUM UNMAP BLOCK DESCRIPTOR COUNT field in the BLOCK LIMITS VPD page.

Since it is unclear how long the UNMAP command will take to execute a '--timeout=' option has been provided. The default timeout period is 60 seconds. If all the logical blocks on a logical unit (e.g. a disk drive) are to be unmapped then the FORMAT UNIT SCSI command (see the sg\_format utility) may be considered as an alternative.

Support for logical block provisioning is indicated by the LBPME bit in the response to the SCSI READ CAPACITY (16) command (see the sg\_readcap utility).

In SBC-3 revision 25 the LBPU and ANC\_SUP bits were added to the Logical Block Provisioning VPD page. When LBPU is set it indicates that the device supports the UNMAP command. When the ANC\_SUP bit is set it indicates the device supports anchored LBAs.

The SCSI UNMAP command does the "right thing" with respect to command queuing. However its ATA counterpart: the DATA SET MANAGEMENT command with the "Trim" bit set does not interact well with SATA queuing known as NCQ. To address this problem T13 have introduced a new command called SFQ DATA SET MANAGEMENT which also has a Trim bit.

## EXAMPLES

In the examples directory of the sg3\_utils package there is a sg\_unmap\_example.txt file that shows the format that the '--in=' option ac?

cepts.

To unmap all blocks from and including LBA 0x2000 to the end of the device (e.g. disk or SSD) with each SCSI UNMAP command given 1024 blocks to unmap:

```
sg_unmap --all=0x2000,1k /dev/sg2
```

Add '--force' to bypass the 15 seconds of warnings. So '--force' is appropriate for batch files.

## EXIT STATUS

The exit status of `sg_unmap` is 0 when it is successful. Otherwise see the `sg3_utils(8)` man page.

## AUTHORS

Written by Douglas Gilbert.

## REPORTING BUGS

Report bugs to <[dgilbert@interlog.com](mailto:dgilbert@interlog.com)>.

## COPYRIGHT

Copyright ? 2009-2018 Douglas Gilbert

This software is distributed under a FreeBSD license. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

## SEE ALSO

`sg_format`, `sg_get_lba_status`, `sg_readcap`, `sg_vpd`, `sg_write_same` (`sg3_utils`)

`sg3_utils-1.43`

March 2018

SG\_UNMAP(8)