



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'snap-discard-ns.8' command

\$ man snap-discard-ns.8

SNAP-DISCARD-NS(5) snappy SNAP-DISCARD-NS(5)

NAME

 snap-discard-ns - internal tool for discarding preserved namespaces of
 snappy applications

SYNOPSIS

 snap-discard-ns [--from-snap-confine] SNAP_INSTANCE_NAME

DESCRIPTION

 The snap-discard-ns is a program used internally by snapd to discard a
 preserved mount namespace of a particular snap.

OPTIONS

 The --from-snap-confine option is used internally by snap-confine to
 tell snap-discard-ns that it is invoked from snap-confine and can dis-
 able locking.

ENVIRONMENT

 snap-discard-ns responds to the following environment variables

 SNAP_CONFINE_DEBUG:

 When defined the program will print additional diagnostic infor?

mation about the actions being performed. All the output goes to stderr.

FILES

snap-discard-ns uses the following files:

`/run/snapd/ns/$SNAP_INSTNACE_NAME.mnt: /run/snapd/ns/$SNAP_INSTNACE_NAME.*.mnt:`

The preserved mount namespace that is unmounted and removed by snap-discard-ns. The second form is for the per-user mount namespace.

`/run/snapd/ns/snap.$SNAP_INSTNACE_NAME.fstab:`

`/run/snapd/ns/snap.$SNAP_INSTNACE_NAME.*.user-fstab:`

The current mount profile of a preserved mount namespace that is removed by snap-discard-ns.

BUGS

Please report all bugs with <https://bugs.launchpad.net/snapd/+filebug>

AUTHOR

zygmunt.krynicki@canonical.com

COPYRIGHT

Canonical Ltd.

2.36

2018-10-17

SNAP-DISCARD-NS(5)