



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'strpbrk.3' command**

**\$ man strpbrk.3**

STRPBRK(3)      Linux Programmer's Manual      STRPBRK(3)

### **NAME**

strpbrk - search a string for any of a set of bytes

### **SYNOPSIS**

```
#include <string.h>

char *strpbrk(const char *s, const char *accept);
```

### **DESCRIPTION**

The strpbrk() function locates the first occurrence in the string s of any of the bytes in the string accept.

### **RETURN VALUE**

The strpbrk() function returns a pointer to the byte in s that matches one of the bytes in accept, or NULL if no such byte is found.

### **ATTRIBUTES**

For an explanation of the terms used in this section, see at?tributes(7).

???

?Interface ? Attribute ? Value ?

???

?strpbrk() ? Thread safety ? MT-Safe ?

???

### **CONFORMING TO**

POSIX.1-2001, POSIX.1-2008, C89, C99, SVr4, 4.3BSD.

### **SEE ALSO**

index(3), memchr(3), rindex(3), strchr(3), string(3), strsep(3), str?  
spn(3), strstr(3), strtok(3), wcspbrk(3)

## COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at  
<https://www.kernel.org/doc/man-pages/>.

2015-08-08

STRPBRK(3)