## Red Hat Enterprise Linux Release 9.2 Manual Pages on 'stty.2' command

### $ man stty.2

UNIMPLEMENTED(2)          Linux Programmer's Manual          UNIMPLEMENTED(2)

NAME

    afs_syscall,  break,  fattach,  fdetach,  ftime, getmsg, getpmsg, gtty,

    isastream, lock, madvise1, mpx, prof, profil,  putmsg,  putpmsg,  secu?

    rity, stty, tuxcall, ulimit, vserver - unimplemented system calls

SYNOPSIS

    Unimplemented system calls.

DESCRIPTION

    These system calls are not implemented in the Linux kernel.

RETURN VALUE

    These system calls always return -1 and set errno to ENOSYS.

NOTES

    Note that ftime(3), profil(3), and ulimit(3) are implemented as library

    functions.

    Some system calls,  like  alloc_hugepages(2),  free_hugepages(2),  iop?

    erm(2), iopl(2), and vm86(2) exist only on certain architectures.

    Some  system  calls, like ipc(2), create_module(2), init_module(2), and

    delete_module(2) exist only when the Linux kernel was built  with  sup?

    port for them.

SEE ALSO

    syscalls(2)

COLOPHON

    This  page  is  part of release 5.10 of the Linux man-pages project.  A

description of the project, information about reporting bugs, and the latest version of this page, can be found at https://www.kernel.org/doc/man-pages/.