



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'sys_siglist.3' command

\$ man sys_siglist.3

STRSIGNSIGNAL(3) Linux Programmer's Manual STRSIGNSIGNAL(3)

NAME

strsignal, sigdescr_np, sigdescr_np, sys_siglist - return string de?

scribing signal

SYNOPSIS

```
#include <string.h>

char *strsignal(int sig);

char *sigdescr_np(int sig);

char *sigabbrev_np(int sig);

extern const char * const sys_siglist[];
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

sigabbrev_np(), sigdescr_np():

_GNU_SOURCE

strsignal():

From glibc 2.10 to 2.31:

_POSIX_C_SOURCE >= 200809L

Before glibc 2.10:

_GNU_SOURCE

sys_siglist:

Since glibc 2.19:

_DEFAULT_SOURCE

Glibc 2.19 and earlier:

_BSD_SOURCE

DESCRIPTION

The `strsignal()` function returns a string describing the signal number passed in the argument `sig`. The string can be used only until the next call to `strsignal()`. The string returned by `strsignal()` is localized according to the `LC_MESSAGES` category in the current locale.

The `sigdescr_np()` function returns a string describing the signal number passed in the argument `sig`. Unlike `strsignal()` this string is not influenced by the current locale.

The `sigabbrev_np()` function returns the abbreviated name of the signal, `sig`. For example, given the value `SIGINT`, it returns the string "INT".

The (deprecated) array `sys_siglist` holds the signal description strings indexed by signal number. The `strsignal()` or the `sigdescr_np()` function should be used instead of this array; see also VERSIONS.

RETURN VALUE

The `strsignal()` function returns the appropriate description string, or an unknown signal message if the signal number is invalid. On some systems (but not on Linux), `NULL` may instead be returned for an invalid signal number.

The `sigdescr_np()` and `sigabbrev_np()` functions return the appropriate description string. The returned string is statically allocated and valid for the lifetime of the program. These functions return `NULL` for an invalid signal number.

VERSIONS

`sigdescr_np()` and `sigabbrev_np()` first appeared in glibc 2.32.

Starting with version 2.32, the `sys_siglist` symbol is no longer exported by glibc.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??
?Interface ? Attribute ? Value ?
??
?strsignal() ? Thread safety ? MT-Unsafe race:strsignal locale ?

??

?sigdescr_np(), ? Thread safety ? MT-Safe ?

?sigabbrev_np() ? ?

??

CONFORMING TO

strsignal(): POSIX.1-2008. Present on Solaris and the BSDs.

sigdescr_np() and sigdabbrev_np() are GNU extensions.

sys_siglist is nonstandard, but present on many other systems.

NOTES

sigdescr_np() and sigdabbrev_np() are thread-safe and async-signal-safe.

SEE ALSO

psignal(3), strerror(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at
<https://www.kernel.org/doc/man-pages/>.

GNU

2020-11-01

STRSIGNSAL(3)