



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'systemd-hostnamed.service.8' command

\$ man systemd-hostnamed.service.8

SYSTEMD-HOSTNAMED.SERVICE(8systemd-hostnamed.serviSYSTEMD-HOSTNAMED.SERVICE(8)

NAME

systemd-hostnamed.service, systemd-hostnamed - Daemon to control system

hostname from programs

SYNOPSIS

systemd-hostnamed.service

/usr/lib/systemd/systemd-hostnamed

DESCRIPTION

systemd-hostnamed.service is a system service that may be used to change the system's hostname and related machine metadata from user programs. It is automatically activated on request and terminates itself when unused.

It currently offers access to five variables:

- ? The current hostname (Example: "dhcp-192-168-47-11")
- ? The static (configured) hostname (Example: "lennarts-computer")
- ? The pretty hostname (Example: "Lennart's Computer")
- ? A suitable icon name for the local host (Example: "computer-laptop")
- ? A chassis type (Example: "tablet")

The static hostname is stored in /etc/hostname, see hostname(5) for more information. The pretty hostname, chassis type, and icon name are stored in /etc/machine-info, see machine-info(5).

The tool hostnamectl(1) is a command line client to this service.

See `org.freedesktop.hostname1(5)` and `org.freedesktop.LogControl1(5)` for a description of the D-Bus API.

SEE ALSO

`systemd(1)`, `hostname(5)`, `machine-info(5)`, `hostnamectl(1)`,

`sethostname(2)`

`systemd` 252

`SYSTEMD-HOSTNAMED.SERVICE(8)`