Red Hat Enterprise Linux Release 9.2 Manual Pages on 'tac.1' command

$ man tac.1

TAC(1)   User Commands   TAC(1)

NAME

   tac - concatenate and print files in reverse

SYNOPSIS

   tac [OPTION]... [FILE]...

DESCRIPTION

   Write each FILE to standard output, last line first.

   With no FILE, or when FILE is -, read standard input.

   Mandatory arguments to long options are mandatory for short options

   too.

   -b, --before

       attach the separator before instead of after

   -r, --regex

       interpret the separator as a regular expression

   -s, --separator=STRING

       use STRING as the separator instead of newline

   --help display this help and exit

   --version

       output version information and exit

AUTHOR

   Written by Jay Lepreau and David MacKenzie.

REPORTING BUGS

   GNU coreutils online help: <https://www.gnu.org/software/coreutils/>

Report any translation bugs to <https://translationproject.org/team/>

COPYRIGHT

Copyright ? 2020 Free Software Foundation, Inc.   License GPLv3+: GNU

GPL version 3 or later <https://gnu.org/licenses/gpl.html>.

This is free software: you are free to change and redistribute it.

There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

rev(1)

Full documentation <https://www.gnu.org/software/coreutils/tac>

or available locally via: info '(coreutils) tac invocation'