



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'tc-fq_codel.8' command

\$ man tc-fq_codel.8

FQ_CoDel(8) Linux FQ_CoDel(8)

NAME

CoDel - Fair Queuing (FQ) with Controlled Delay (CoDel)

SYNOPSIS

```
tc qdisc ... fq_codel [ limit PACKETS ] [ flows NUMBER ] [ target TIME
] [ interval TIME ] [ quantum BYTES ] [ ecn | noecn ] [ ce_threshold
TIME ] [ ce_threshold_selector VALUE/MASK ] [ memory_limit BYTES ]
```

DESCRIPTION

FQ_Codel (Fair Queuing Controlled Delay) is queuing discipline that combines Fair Queuing with the CoDel AQM scheme. FQ_Codel uses a stochastic model to classify incoming packets into different flows and is used to provide a fair share of the bandwidth to all the flows using the queue. Each such flow is managed by the CoDel queuing discipline. Reordering within a flow is avoided since Codel internally uses a FIFO queue.

PARAMETERS

limit

has the same semantics as codel and is the hard limit on the real queue size. When this limit is reached, incoming packets are dropped. Default is 10240 packets.

memory_limit

sets a limit on the total number of bytes that can be queued in this FQ-CoDel instance. The lower of the packet limit of the limit parameter

and the memory limit will be enforced. Default is 32 MB.

flows

is the number of flows into which the incoming packets are classified.

Due to the stochastic nature of hashing, multiple flows may end up being hashed into the same slot. Newer flows have priority over older ones. This parameter can be set only at load time since memory has to be allocated for the hash table. Default value is 1024.

target

has the same semantics as codel and is the acceptable minimum standing/persistent queue delay. This minimum delay is identified by tracking the local minimum queue delay that packets experience. Default value is 5ms.

interval

has the same semantics as codel and is used to ensure that the measured minimum delay does not become too stale. The minimum delay must be experienced in the last epoch of length interval. It should be set on the order of the worst-case RTT through the bottleneck to give endpoints sufficient time to react. Default value is 100ms.

quantum

is the number of bytes used as 'deficit' in the fair queuing algorithm. Default is set to 1514 bytes which corresponds to the Ethernet MTU plus the hardware header length of 14 bytes.

ecn | noecn

has the same semantics as codel and can be used to mark packets instead of dropping them. If ecn has been enabled, noecn can be used to turn it off and vice-a-versa. Unlike codel, ecn is turned on by default.

ce_threshold

sets a threshold above which all packets are marked with ECN Congestion Experienced. This is useful for DCTCP-style congestion control algorithms that require marking at very shallow queueing thresholds.

ce_threshold_selector

sets a filter so that the ce_threshold feature is applied to only a subset of the traffic seen by the qdisc. If set, the MASK value will be

applied as a bitwise AND to the diffserv/ECN byte of the IP header, and only if the result of this masking equals VALUE, will the ce_threshold logic be applied to the packet.

drop_batch

sets the maximum number of packets to drop when limit or memory_limit is exceeded. Default value is 64.

EXAMPLES

```
#tc qdisc add dev eth0 root fq_codel

#tc -s qdisc show

qdisc fq_codel 8002: dev eth0 root refcnt 2 limit 10240p flows 1024
quantum 1514
target 5.0ms interval 100.0ms ecn
Sent 428514 bytes 2269 pkt (dropped 0, overlimits 0 requeues 0)
backlog 0b 0p requeues 0
maxpacket 256 drop_overlimit 0 new_flow_count 0 ecn_mark 0
new_flows_len 0 old_flows_len 0

#tc qdisc add dev eth0 root fq_codel limit 2000 target 3ms interval
40ms noecn

#tc -s qdisc show

qdisc fq_codel 8003: dev eth0 root refcnt 2 limit 2000p flows 1024
quantum 1514 target 3.0ms interval 40.0ms
Sent 2588985006 bytes 1783629 pkt (dropped 0, overlimits 0 requeues
34869)
backlog 0b 0p requeues 34869
maxpacket 65226 drop_overlimit 0 new_flow_count 73 ecn_mark 0
new_flows_len 1 old_flows_len 3
```

SEE ALSO

tc(8), tc-codel(8), tc-red(8)

AUTHORS

FQ_CoDel was implemented by Eric Dumazet. This manpage was written by Vijay Subramanian. Please report corrections to the Linux Networking mailing list <netdev@vger.kernel.org>.