



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'tipc-media.8' command

\$ man tipc-media.8

TIPC-MEDIA(8) Linux TIPC-MEDIA(8)

NAME

tipc-media - list or modify media properties

SYNOPSIS

tipc media set { priority PRIORITY | tolerance TOLERANCE | window WIN?

DOW } media MEDIA

tipc media get { priority | tolerance | window } media MEDIA

tipc media list

OPTIONS

Options (flags) that can be passed anywhere in the command chain.

-h, --help

Show help about last valid command. For example tipc media

--help will show media help and tipc --help will show general

help. The position of the option in the string is irrelevant.

DESCRIPTION

Media properties

priority

Default link priority inherited by all bearers subsequently en?

abled on a media. For more info about link priority see tipc-

link(8)

tolerance

Default link tolerance inherited by all bearers subsequently en?

abled on a media. For more info about link tolerance see tipc-

link(8)

window

Default link window inherited by all bearers subsequently enabled on a media. For more info about link window see tipc-

link(8)

EXIT STATUS

Exit status is 0 if command was successful or a positive integer upon failure.

SEE ALSO

tipc(8), tipc-bearer(8), tipc-link(8), tipc-nametable(8), tipc-node(8), tipc-peer(8), tipc-socket(8)

REPORTING BUGS

Report any bugs to the Network Developers mailing list <net?dev@vger.kernel.org> where the development and maintenance is primarily done. You do not have to be subscribed to the list to send a message there.

AUTHOR

Richard Alpe <richard.alpe@ericsson.com>

iproute2

02 Jun 2015

TIPC-MEDIA(8)