



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'tolower_1.3' command

\$ man tolower_1.3

TOWLOWER(3) Linux Programmer's Manual TOWLOWER(3)

NAME

tolower, tolower_l - convert a wide character to lowercase

SYNOPSIS

```
#include <wctype.h>
```

```
wint_t tolower(wint_t wc);
```

```
wint_t tolower_l(wint_t wc, locale_t locale);
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

tolower_l():

Since glibc 2.10:

```
  _XOPEN_SOURCE >= 700
```

Before glibc 2.10:

```
  _GNU_SOURCE
```

DESCRIPTION

The tolower() function is the wide-character equivalent of the tolower(3) function. If wc is an uppercase wide character, and there exists a lowercase equivalent in the current locale, it returns the lowercase equivalent of wc. In all other cases, wc is returned unchanged.

The tolower_l() function performs the same task, but performs the conversion based on the character type information in the locale specified by locale. The behavior of tolower_l() is undefined if locale is the special locale object LC_GLOBAL_LOCALE (see duplocale(3)) or is not a

valid locale object handle.

The argument wc must be representable as a wchar_t and be a valid character in the locale or be the value WEOF.

RETURN VALUE

If wc was convertible to lowercase, towlower() returns its lowercase equivalent; otherwise it returns wc.

VERSIONS

The towlower_l() function first appeared in glibc 2.3.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?tolower() ? Thread safety ? MT-Safe locale ?

??

?tolower_l() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

tolower(): C99, POSIX.1-2001 (XSI); present as an XSI extension in POSIX.1-2008, but marked obsolete.

towlower_l(): POSIX.1-2008.

NOTES

The behavior of these functions depends on the LC_CTYPE category of the locale.

These functions are not very appropriate for dealing with Unicode characters, because Unicode knows about three cases: upper, lower and title case.

SEE ALSO

iswlower(3), towctrans(3), towupper(3), locale(7)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the

latest version of this page, can be found at

<https://www.kernel.org/doc/man-pages/>.

GNU

2017-09-15

TOWLOWER(3)