



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'ungetwc.3' command

\$ man ungetwc.3

UNGETWC(3) Linux Programmer's Manual UNGETWC(3)

NAME

ungetwc - push back a wide character onto a FILE stream

SYNOPSIS

```
#include <wchar.h>

wint_t ungetwc(wint_t wc, FILE *stream);
```

DESCRIPTION

The `ungetwc()` function is the wide-character equivalent of the `ungetc(3)` function. It pushes back a wide character onto stream and returns it.

If `wc` is `WEOF`, it returns `WEOF`. If `wc` is an invalid wide character, it sets `errno` to `EILSEQ` and returns `WEOF`.

If `wc` is a valid wide character, it is pushed back onto the stream and thus becomes available for future wide-character read operations. The file-position indicator is decremented by one or more. The end-of-file indicator is cleared. The backing storage of the file is not affected.

Note: `wc` need not be the last wide-character read from the stream; it can be any other valid wide character.

If the implementation supports multiple push-back operations in a row, the pushed-back wide characters will be read in reverse order; however, only one level of push-back is guaranteed.

RETURN VALUE

The `ungetwc()` function returns `wc` when successful, or `WEOF` upon fail?

ure.

ATTRIBUTES

For an explanation of the terms used in this section, see at? tributes(7).

??

?Interface ? Attribute ? Value ?

??

?ungetwc() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

NOTES

The behavior of ungetwc() depends on the LC_CTYPE category of the current locale.

SEE ALSO

fgetwc(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.