



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'xfs_mdrestore.8' command

\$ man xfs_mdrestore.8

xfs_mdrestore(8) System Manager's Manual xfs_mdrestore(8)

NAME

xfs_mdrestore - restores an XFS metadump image to a filesystem image

SYNOPSIS

xfs_mdrestore [-gi] source target

xfs_mdrestore -i source

xfs_mdrestore -V

DESCRIPTION

xfs_mdrestore is a debugging tool that restores a metadata image generated by xfs_metadump(8) to a filesystem. The source argument specifies the location of the metadump image and the target argument specifies the destination for the filesystem image. If the source is -, then the metadata image is read from stdin. This allows the output of another program such as a compression application to be redirected to xfs_mdrestore. The target can be either a file or a device. xfs_mdrestore should not be used to restore metadata onto an existing filesystem unless you are completely certain the target can be destroyed.

OPTIONS

- g Shows restore progress on stdout.
- i Shows metadump information on stdout. If no target is specified, exits after displaying information. Older metadumps may not include any descriptive information.

-V Prints the version number and exits.

DIAGNOSTICS

xfs_mdrestore returns an exit code of 0 if all the metadata is success?
fully restored or 1 if an error occurs.

SEE ALSO

xfs_metadump(8), xfs_repair(8), xfs(5)

BUGS

Email bug reports to linux-xfs@vger.kernel.org.

xfs_mdrestore(8)