



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command '__ppc_get_timebase_freq.3'

\$ man __ppc_get_timebase_freq.3

`__PPC_GET_TIMEBASE(3)` Linux Programmer'sManual `__PPC_GET_TIMEBASE(3)`

NAME

`__ppc_get_timebase`, `__ppc_get_timebase_freq` - get the current value of the Time Base Register on Power architecture and its frequency.

SYNOPSIS

```
#include <sys/platform/ppc.h>

uint64_t __ppc_get_timebase(void)

uint64_t __ppc_get_timebase_freq(void);
```

DESCRIPTION

`__ppc_get_timebase()` reads the current value of the Time Base Register and returns its value, while `__ppc_get_timebase_freq()` returns the frequency in which the Time Base Register is updated.

The Time Base Register is a 64-bit register provided by Power Architecture processors. It stores a monotonically incremented value that is updated at a system-dependent frequency that may be different from the processor frequency.

RETURN VALUE

`__ppc_get_timebase()` returns a 64-bit unsigned integer that represents

the current value of the Time Base Register.

`__ppc_get_timebase_freq()` returns a 64-bit unsigned integer that represents the frequency at which the Time Base Register is updated.

VERSIONS

GNU C Library support for `__ppc_get_timebase()` has been provided since version 2.16 and `__ppc_get_timebase_freq()` has been available since version 2.17.

CONFORMING TO

Both functions are nonstandard GNU extensions.

EXAMPLES

The following program will calculate the time, in microseconds, spent between two calls to `__ppc_get_timebase()`.

Program source

```
#include <inttypes.h>
#include <stdint.h>
#include <stdio.h>
#include <stdlib.h>
#include <sys/platform/ppc.h>

/* Maximum value of the Time Base Register: 2^60 - 1.
   Source: POWER ISA. */
#define MAX_TB 0xFFFFFFFFFFFFFFFF

int
main(void)
{
    uint64_t tb1, tb2, diff;
    uint64_t freq = __ppc_get_timebase_freq();
    printf("Time Base frequency = %"PRIu64" Hz\n", freq);
    tb1 = __ppc_get_timebase();
    // Do some stuff...
    tb2 = __ppc_get_timebase();
    if (tb2 > tb1) {
        diff = tb2 - tb1;
    } else {
```

```
/* Treat Time Base Register overflow. */
diff = (MAX_TB - tb2) + tb1;
}
printf("Elapsed time = %1.2f usecs\n",
      (double) diff * 1000000 / freq );
exit(EXIT_SUCCESS);
}
```

SEE ALSO

time(2), usleep(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU C Library 2020-06-09 __PPC_GET_TIMEBASE(3)