



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'autrace.8'

\$ man autrace.8

AUTRACE(8) System Administration Utilities AUTRACE(8)

NAME

autrace - a program similar to strace

SYNOPSIS

autrace program [-r] [program-args]...

DESCRIPTION

autrace is a program that will add the audit rules to trace a process similar to strace. It will then execute the program passing arguments to it. The resulting audit information will be in the audit logs if the audit daemon is running or syslog. This command deletes all audit rules prior to executing the target program and after executing it. As a safety precaution, it will not run unless all rules are deleted with auditctl prior to use.

OPTIONS

-r Limit syscalls collected to ones needed for analyzing resource usage. This could help people doing threat modeling. This saves space in logs.

EXAMPLES

The following illustrates a typical session:

```
autrace /bin/ls /tmp
```

```
ausearch --start recent -p 2442 -i
```

and for resource usage mode:

```
autrace -r /bin/ls
```

```
ausearch --start recent -p 2450 --raw | aureport --file --summary
```

```
ausearch --start recent -p 2450 --raw | aureport --host --summary
```

SEE ALSO

ausearch(8), auditctl(8).

AUTHOR

Steve Grubb

Red Hat

Jan 2007

AUTRACE(8)