



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'bcopy.3'

\$ man bcopy.3

BCOPY(3) Linux Programmer's Manual BCOPY(3)

NAME

bcopy - copy byte sequence

SYNOPSIS

```
#include <strings.h>

void bcopy(const void *src, void *dest, size_t n);
```

DESCRIPTION

The bcopy() function copies n bytes from src to dest. The result is correct, even when both areas overlap.

RETURN VALUE

None.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

```
????????????????????????????????????????????????????????
?Interface ? Attribute ? Value ?
????????????????????????????????????????????????????????
?bcopy() ? Thread safety ? MT-Safe ?
```

??

CONFORMING TO

4.3BSD. This function is deprecated (marked as LEGACY in POSIX.1-2001): use `memcpy(3)` or `memmove(3)` in new programs. Note that the first two arguments are interchanged for `memcpy(3)` and `memmove(3)`.
POSIX.1-2008 removes the specification of `bcopy()`.

SEE ALSO

`bstring(3)`, `memccpy(3)`, `memcpy(3)`, `memmove(3)`, `strcpy(3)`, `strncpy(3)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux 2017-03-13 BCOPY(3)