



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'buildah-logout.1'

\$ man buildah-logout.1

buildah-logout(1) General Commands Manual buildah-logout(1)

NAME

buildah-logout - Logout of a container registry

SYNOPSIS

buildah logout [options] registry

DESCRIPTION

buildah logout logs out of a specified registry server by deleting the cached credentials stored in the auth.json file. The path of the authentication file can be overridden by the user by setting the authfile flag. The default path used is ``${XDG_RUNTIME_DIR}/containers/auth.json``. If `XDG_RUNTIME_DIR` is not set, the default is `"/run/containers/$UID/auth.json"`. All the cached credentials can be removed by setting the all flag.

buildah [GLOBAL OPTIONS]

buildah logout [GLOBAL OPTIONS]

buildah logout [OPTIONS] REGISTRY [GLOBAL OPTIONS]

OPTIONS

--all, -a

Remove the cached credentials for all registries in the auth file

`--authfile`

Path of the authentication file. Default is `$(XDG_RUNTIME_DIR)/con?`

ainers/auth.json. If `XDG_RUNTIME_DIR` is not set, the default is

`/run/containers/$UID/auth.json`.

Note: You can also override the default path of the authentication file

by setting the `REGISTRY_AUTH_FILE` environment variable. `export REG?`

`ISTRY_AUTH_FILE=path`

`--help, -h`

Print usage statement

EXAMPLES

```
$ buildah logout quay.io
```

Removed login credentials for quay.io

```
$ buildah logout --authfile authdir/myauths.json quay.io
```

Removed login credentials for quay.io

```
$ buildah logout --all
```

Remove login credentials for all registries

SEE ALSO

[buildah\(1\)](#), [buildah-login\(1\)](#)

[buildah](#)

Apr 2019

[buildah-logout\(1\)](#)