



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'bundle-add.1'***

**\$ man bundle-add.1**

BUNDLE-ADD(1) BUNDLE-ADD(1)

#### **NAME**

bundle-add - Add gem to the Gemfile and run bundle install

#### **SYNOPSIS**

```
bundle add GEM_NAME [--group=GROUP] [--version=VERSION]
[--source=SOURCE] [--git=GIT] [--branch=BRANCH] [--skip-install]
[--strict] [--optimistic]
```

#### **DESCRIPTION**

Adds the named gem to the Gemfile and run bundle install. bundle in?

stall can be avoided by using the flag --skip-install.

Example:

```
bundle add rails
```

```
bundle add rails --version "< 3.0, > 1.1"
```

```
bundle add rails --version "~> 5.0.0" --source "https://gems.example.com" --group "development"
```

```
bundle add rails --skip-install
```

```
bundle add rails --group "development, test"
```

## OPTIONS

--version, -v

Specify version requirements(s) for the added gem.

--group, -g

Specify the group(s) for the added gem. Multiple groups should be separated by commas.

--source, , -s

Specify the source for the added gem.

--git Specify the git source for the added gem.

--branch

Specify the git branch for the added gem.

--skip-install

Adds the gem to the Gemfile but does not install it.

--optimistic

Adds optimistic declaration of version

--strict

Adds strict declaration of version

December 2021

BUNDLE-ADD(1)