



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'bundle.1'

\$ man bundle.1

BUNDLE(1)

BUNDLE(1)

NAME

bundle - Ruby Dependency Management

SYNOPSIS

bundle COMMAND [--no-color] [--verbose] [ARGS]

DESCRIPTION

Bundler manages an application's dependencies through its entire life across many machines systematically and repeatably.

See the bundler website <https://bundler.io> for information on getting started, and Gemfile(5) for more information on the Gemfile format.

OPTIONS

--no-color

Print all output without color

--retry, -r

Specify the number of times you wish to attempt network commands

--verbose, -V

Print out additional logging information

BUNDLE COMMANDS

We divide bundle subcommands into primary commands and utilities:

PRIMARY COMMANDS

`bundle install(1)` [bundle-install.1.html](#)

Install the gems specified by the Gemfile or Gemfile.lock

`bundle update(1)` [bundle-update.1.html](#)

Update dependencies to their latest versions

`bundle package(1)` [bundle-package.1.html](#)

Package the `.gem` files required by your application into the vendor/cache directory

`bundle exec(1)` [bundle-exec.1.html](#)

Execute a script in the current bundle

`bundle config(1)` [bundle-config.1.html](#)

Specify and read configuration options for Bundler

`bundle help(1)`

Display detailed help for each subcommand

UTILITIES

`bundle add(1)` [bundle-add.1.html](#)

Add the named gem to the Gemfile and run `bundle install`

`bundle binstubs(1)` [bundle-binstubs.1.html](#)

Generate binstubs for executables in a gem

`bundle check(1)` [bundle-check.1.html](#)

Determine whether the requirements for your application are in? stalled and available to Bundler

`bundle show(1)` [bundle-show.1.html](#)

Show the source location of a particular gem in the bundle

`bundle outdated(1)` [bundle-outdated.1.html](#)

Show all of the outdated gems in the current bundle

`bundle console(1)`

Start an IRB session in the current bundle

`bundle open(1)` [bundle-open.1.html](#)

Open an installed gem in the editor

`bundle lock(1)` [bundle-lock.1.html](#)

Generate a lockfile for your dependencies

bundle viz(1) bundle-viz.1.html

Generate a visual representation of your dependencies

bundle init(1) bundle-init.1.html

Generate a simple Gemfile, placed in the current directory

bundle gem(1) bundle-gem.1.html

Create a simple gem, suitable for development with Bundler

bundle platform(1) bundle-platform.1.html

Display platform compatibility information

bundle clean(1) bundle-clean.1.html

Clean up unused gems in your Bundler directory

bundle doctor(1) bundle-doctor.1.html

Display warnings about common problems

bundle remove(1) bundle-remove.1.html

Removes gems from the Gemfile

PLUGINS

When running a command that isn't listed in PRIMARY COMMANDS or UTILITIES, Bundler will try to find an executable on your path named `bundler-<command>` and execute it, passing down any extra arguments to it.

OBSOLETE

These commands are obsolete and should no longer be used:

? `bundle cache(1)`

? `bundle show(1)`

December 2021

BUNDLE(1)