



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'cancel.1'***

#### ***\$ man cancel.1***

cancel(1)                    OpenPrinting                    cancel(1)

#### NAME

cancel - cancel jobs

#### SYNOPSIS

cancel [ -h hostname[:port] ] [ -E ] [ -U username ] [ -a ] [ -u user?  
name ] [ -x ] [ id ] [ destination ] [ destination-id ]

#### DESCRIPTION

The cancel command cancels print jobs. If no destination or id is specified, the currently printing job on the default destination is canceled.

#### OPTIONS

The following options are recognized by cancel:

- a Cancel all jobs on the named destination, or all jobs on all destinations if none is provided.
- E Forces encryption when connecting to the server.
- h hostname[:port]  
Specifies an alternate server. Note: This option must occur before all others.

-U username

Specifies the username to use when connecting to the server.

-u username

Cancels jobs owned by username.

-x Deletes job data files in addition to canceling.

## CONFORMING TO

Unlike the System V printing system, CUPS allows printer names to contain any printable character except SPACE, TAB, "/", or "#". Also, printer and class names are not case-sensitive.

## EXAMPLES

Cancel the current print job:

```
cancel
```

Cancel job "myprinter-42":

```
cancel myprinter-42
```

Cancel all jobs:

```
cancel -a
```

## NOTES

Administrators wishing to prevent unauthorized cancellation of jobs via the -u option should require authentication for Cancel-Jobs operations in cupsd.conf(5).

## SEE ALSO

cupsd.conf(5), lp(1), lpmove(8), lpstat(1), CUPS Online Help (<http://localhost:631/help>)

## COPYRIGHT

Copyright ? 2007-2019 by Apple Inc.

2022-05-02

CUPS

cancel(1)