



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'chown.1'

\$ man chown.1

CHOWN(1) User Commands CHOWN(1)

NAME

chown - change file owner and group

SYNOPSIS

chown [OPTION]... [OWNER][:[GROUP]] FILE...

chown [OPTION]... --reference=RFILE FILE...

DESCRIPTION

This manual page documents the GNU version of chown. chown changes the user and/or group ownership of each given file. If only an owner (a user name or numeric user ID) is given, that user is made the owner of each given file, and the files' group is not changed. If the owner is followed by a colon and a group name (or numeric group ID), with no spaces between them, the group ownership of the files is changed as well. If a colon but no group name follows the user name, that user is made the owner of the files and the group of the files is changed to that user's login group. If the colon and group are given, but the owner is omitted, only the group of the files is changed; in this case, chown performs the same function as chgrp. If only a colon is given,

or if the entire operand is empty, neither the owner nor the group is changed.

OPTIONS

Change the owner and/or group of each FILE to OWNER and/or GROUP. With

--reference, change the owner and group of each FILE to those of RFILE.

-c, --changes

like verbose but report only when a change is made

-f, --silent, --quiet

suppress most error messages

-v, --verbose

output a diagnostic for every file processed

--dereference

affect the referent of each symbolic link (this is the default),
rather than the symbolic link itself

-h, --no-dereference

affect symbolic links instead of any referenced file (useful
only on systems that can change the ownership of a symlink)

--from=CURRENT_OWNER:CURRENT_GROUP

change the owner and/or group of each file only if its current
owner and/or group match those specified here. Either may be
omitted, in which case a match is not required for the omitted
attribute

--no-preserve-root

do not treat '/' specially (the default)

--preserve-root

fail to operate recursively on '/'

--reference=RFILE

use RFILE's owner and group rather than specifying OWNER:GROUP
values

-R, --recursive

operate on files and directories recursively

The following options modify how a hierarchy is traversed when the -R
option is also specified. If more than one is specified, only the fi?

nal one takes effect.

-H if a command line argument is a symbolic link to a directory,

traverse it

-L traverse every symbolic link to a directory encountered

-P do not traverse any symbolic links (default)

--help display this help and exit

--version

output version information and exit

Owner is unchanged if missing. Group is unchanged if missing, but

changed to login group if implied by a ':' following a symbolic OWNER.

OWNER and GROUP may be numeric as well as symbolic.

EXAMPLES

```
chown root /u
```

Change the owner of /u to "root".

```
chown root:staff /u
```

Likewise, but also change its group to "staff".

```
chown -hR root /u
```

Change the owner of /u and subfiles to "root".

AUTHOR

Written by David MacKenzie and Jim Meyering.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report any translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright ? 2020 Free Software Foundation, Inc. License GPLv3+: GNU

GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it.

There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

chown(2)

Full documentation <<https://www.gnu.org/software/coreutils/chown>>

or available locally via: info '(coreutils) chown invocation'