



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'copysignl.3'

\$ man copysignl.3

COPYSIGN(3) Linux Programmer's Manual COPYSIGN(3)

NAME

copysign, copysignf, copysignl - copy sign of a number

SYNOPSIS

```
#include <math.h>
```

```
double copysign(double x, double y);
```

```
float copysignf(float x, float y);
```

```
long double copysignl(long double x, long double y);
```

Link with -lm.

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

```
copysign(), copysignf(), copysignl():
```

```
  _ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

```
  || /* Since glibc 2.19: */ _DEFAULT_SOURCE
```

```
  || /* Glibc versions <= 2.19: */ _BSD_SOURCE || _SVID_SOURCE
```

DESCRIPTION

These functions return a value whose absolute value matches that of x, but whose sign bit matches that of y.

For example, copysign(42.0, -1.0) and copysign(-42.0, -1.0) both return

-42.0.

RETURN VALUE

On success, these functions return a value whose magnitude is taken from x and whose sign is taken from y.

If x is a NaN, a NaN with the sign bit of y is returned.

ERRORS

No errors occur.

ATTRIBUTES

For an explanation of the terms used in this section, see at?

tributes(7).

??

?Interface ? Attribute ? Value ?

??

?copysign(), copysignf(), copysignl() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008. This function is defined in IEC 559 (and the appendix with recommended functions in IEEE 754/IEEE 854).

NOTES

On architectures where the floating-point formats are not IEEE 754 compliant, these functions may treat a negative zero as positive.

SEE ALSO

signbit(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.