



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'crypt_checksalt.3'

\$ man crypt_checksalt.3

CRYPT_CHECKSALT(3) BSD Library Functions Manual CRYPT_CHECKSALT(3)

NAME

crypt_checksalt ? validate a crypt setting string

LIBRARY

Crypt Library (libcrypt, -lcrypt)

SYNOPSIS

```
#include <crypt.h>
```

```
int
```

```
crypt_checksalt(const char *setting);
```

DESCRIPTION

crypt_checksalt checks the setting string against the system configuration and reports whether the hashing method and parameters it specifies are acceptable. It is intended to be used by programs such as login(1)

to determine whether the user's passphrase should be re-hashed using the currently preferred hashing method.

RETURN VALUES

The return value is 0 if there is nothing wrong with this setting. Otherwise, it is one of the following constants:

CRYPT_SALT_OK

setting is a fully correct setting string. This constant is guaranteed to equal 0.

CRYPT_SALT_INVALID

setting is not a valid setting string; either it specifies a hashing method that is not known to this version of libxcrypt, or it specifies invalid parameters for the method.

CRYPT_SALT_METHOD_DISABLED (Not implemented, yet)

setting specifies a hashing method that is no longer allowed to be used at all; crypt will fail if passed this setting. Manual intervention will be required to reactivate the user's account.

CRYPT_SALT_METHOD_LEGACY (Not implemented, yet)

setting specifies a hashing method that is no longer considered strong enough for use with new passphrases. crypt will still authenticate a passphrase against this setting, but if authentication succeeds, the passphrase should be re-hashed using the currently preferred method.

CRYPT_SALT_TOO_CHEAP (Not implemented, yet)

setting specifies cost parameters that are considered too cheap for use with new passphrases. crypt will still authenticate a passphrase against this setting, but if authentication succeeds, the passphrase should be re-hashed using the currently preferred

method.

FEATURE TEST MACROS

<crypt.h> will define the macro CRYPT_CHECKSALT_AVAILABLE if crypt_checksalt is available in the current version of libxcrypt.

BUGS

Since full configurability is not yet implemented, the current implementation will only ever return CRYPT_SALT_OK (0) or CRYPT_SALT_INVALID when invoked.

PORTABILITY NOTES

The function crypt_checksalt is not part of any standard. It was added to libxcrypt in version 4.3.0.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?crypt_checksalt ? Thread safety ? MT-Safe ?

??

SEE ALSO

crypt(3), crypt_gensalt(3), crypt(5)