



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'cryptsetup-luksHeaderRestore.8'***

***\$ man cryptsetup-luksHeaderRestore.8***

CRYPTSETUP-LUKSHEADERRESTORE(Maintenance CommanCRYPTSETUP-LUKSHEADERRESTORE(8)

#### NAME

cryptsetup-luksHeaderRestore - restore a binary backup of the LUKS header and keyslot area

#### SYNOPSIS

cryptsetup luksHeaderRestore --header-backup-file <file> [<options>]  
<device>

#### DESCRIPTION

Restores a binary backup of the LUKS header and keyslot area from the specified file.

NOTE: Using '-' as filename reads the header backup from a file named '-'.

<options> can be [--header, --header-backup-file, --disable-locks].

WARNING: Header and keyslots will be replaced, only the passphrases from the backup will work afterward.

This command requires that the volume key size and data offset of the LUKS header already on the device and of the header backup match.

Alternatively, if there is no LUKS header on the device, the backup

will also be written to it.

## OPTIONS

`--header <device or file storing the LUKS header>`

Use a detached (separated) metadata device or file where the LUKS header is stored. This option allows one to store ciphertext and LUKS header on different devices.

For commands that change the LUKS header (e.g. `luksAddKey`), specify the device or file with the LUKS header directly as the LUKS device.

`--header-backup-file <file>`

Specify file with header backup file.

`--disable-locks`

Disable lock protection for metadata on disk. This option is valid only for LUKS2 and ignored for other formats.

WARNING: Do not use this option unless you run `cryptsetup` in a restricted environment where locking is impossible to perform (where `/run` directory cannot be used).

`--batch-mode, -q`

Suppresses all confirmation questions. Use with care!

If the `--verify-passphrase` option is not specified, this option also switches off the passphrase verification.

`--debug` or `--debug-json`

Run in debug mode with full diagnostic logs. Debug output lines are always prefixed by `#`.

If `--debug-json` is used, additional LUKS2 JSON data structures are printed.

`--version, -V`

Show the program version.

`--usage`

Show short option help.

`--help, -?`

Show help text and default parameters. == REPORTING BUGS

Report bugs at `cryptsetup` mailing list `<cryptsetup@lists.linux.dev>` or

in Issues project section

<https://gitlab.com/cryptsetup/cryptsetup/-/issues/new>.

Please attach output of the failed command with --debug option added.

#### SEE ALSO

Cryptsetup FAQ

<https://gitlab.com/cryptsetup/cryptsetup/wikis/FrequentlyAskedQuestions>

cryptsetup(8), integritysetup(8) and veritysetup(8)

#### CRYPTSETUP

Part of cryptsetup project <https://gitlab.com/cryptsetup/cryptsetup/>.

cryptsetup 2.6.0

2022-12-14 CRYPTSETUP-LUKSHEADERRESTORE(8)