



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'devlink-resource.8'

\$ man devlink-resource.8

DEVLINK-RESOURCE(8) Linux DEVLINK-RESOURCE(8)

NAME

devlink-resource - devlink device resource configuration

SYNOPSIS

devlink [OPTIONS] resource { COMMAND | help }

OPTIONS := { -v[erbose] }

devlink resource show DEV

devlink resource help

devlink resource set DEV path RESOURCE_PATH size RESOURCE_SIZE

DESCRIPTION

devlink resource show - display devlink device's resosources

DEV - specifies the devlink device to show.

Format is:

BUS_NAME/BUS_ADDRESS

devlink resource set - sets resource size of specific resource

DEV - specifies the devlink device.

path RESOURCE_PATH

Resource's path.

size RESOURCE_SIZE

The new resource's size.

EXAMPLES

```
devlink resource show pci/0000:01:00.0
```

Shows the resources of the specified devlink device.

```
devlink resource set pci/0000:01:00.0 /kvd/linear 98304
```

Sets the size of the specified resource for the specified devlink device.

SEE ALSO

devlink(8), devlink-port(8), devlink-sb(8), devlink-monitor(8),

AUTHOR

Arkadi Sharshesky <arkadis@mellanox.com>