



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'diffpp.1'

\$ man diffpp.1

DIFFPP(1) DIFFPP DIFFPP(1)

NAME

diffpp - pretty-print diff outputs with GNU enscript

SYNOPSIS

diffpp currentfile < diff-file

DESCRIPTION

Diffpp converts diff(1)-program's output files to a format suitable to be printed with GNU enscript(1). Program annotates the changes with enscript's special escapes so enscript can highlight the modifications of the file. All changed and added lines are printed with gray-background, deleted lines are marked with minus (^-) characters; diffpp prints one minus character for each deleted line.

EXAMPLES

The easiest way to use diffpp is to use it as an input filter for en?

script. If an input filter is specified for `enscript` it is used to pre-process the incoming data-stream. Filtering does not alter any header strings or file-timestamps which might be printed on `enscript` headers; only the incoming data is modified.

```
enscript -G2re --filter='rcsdiff %s | diffpp %s' *.c *.h
```

Print the changes between current source files and their latest RCS-versions.

```
enscript -G2re --filter='diff %s~ %s | diffpp %s' *.c *.h
```

Print changes between source files and the corresponding backup-files.

SEE ALSO

`diff(1)`, `enscript(1)`

AUTHOR

Markku Rossi <mtr@iki.fi> <<http://www.iki.fi/~mtr/>>

DIFFPP

Jan 29, 1997

DIFFPP(1)