



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'dnf-download.8'

\$ man dnf-download.8

DNF-DOWNLOAD(8) dnf-plugins-core DNF-DOWNLOAD(8)

NAME

dnf-download - DNF download Plugin

Download binary or source packages.

SYNOPSIS

dnf download [options] <pkg-spec>...

ARGUMENTS

<pkg-spec>

Package specification for the package to download. Local RPMs can be specified as well. This is useful with the --source option or if you want to download the same RPM again.

OPTIONS

All general DNF options are accepted, see Options in dnf(8) for details.

tails.

--help-cmd

Show this help.

--arch <arch>[,<arch>...]

Limit the query to packages of given architectures (default is all compatible architectures with your system). To download packages with arch incompatible with your system use --forcearch=<arch> option to change basearch.

--source

Download the source rpm. Enables source repositories of all enabled binary repositories.

--debuginfo

Download the debuginfo rpm. Enables debuginfo repositories of all enabled binary repositories.

--downloaddir

Download directory, default is the current directory (the directory must exist).

--url Instead of downloading, print list of urls where the rpms can be downloaded.

--urlprotocol

Limit the protocol of the urls output by the --url option. Options are http, https, rsync, ftp.

--resolve

Resolves dependencies of specified packages and downloads missing dependencies in the system.

`--alldeps`

When used with `--resolve`, download all dependencies (do not skip already installed ones).

EXAMPLES

`dnf download dnf`

Download the latest dnf package to the current directory.

`dnf download --url dnf`

Just print the remote location url where the dnf rpm can be downloaded from.

`dnf download --url --urlprotocols=https --urlprotocols=rsync dnf`

Same as above, but limit urls to https or rsync urls.

`dnf download dnf --destdir /tmp/dnl`

Download the latest dnf package to the /tmp/dnl directory (the directory must exist).

`dnf download dnf --source`

Download the latest dnf source package to the current directory.

`dnf download rpm --debuginfo`

Download the latest rpm-debuginfo package to the current directory.

`dnf download btanks --resolve`

Download the latest btanks package and the uninstalled dependencies to the current directory.

AUTHOR

See AUTHORS in your Core DNF Plugins distribution

COPYRIGHT

2023, Red Hat, Licensed under GPLv2+

4.3.0

Mar 15, 2023

DNF-DOWNLOAD(8)