



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'dnf-repograph.8'***

**\$ man dnf-repograph.8**

DNF-REPOGRAPH(8)          dnf-plugins-core          DNF-REPOGRAPH(8)

#### NAME

dnf-repograph - DNF repograph Plugin

Output a full package dependency graph in dot format.

#### SYNOPSIS

dnf repograph [<options>] dnf repo-graph [<options>]

#### DESCRIPTION

repograph is a program that generates a full package dependency list from a repository and outputs it in dot format.

#### Options

All general DNF options are accepted, see Options in dnf(8) for details.

`--repo <repoid>`

Specify repo ids to query, can be specified multiple times (default is all enabled).

## EXAMPLES

Output dependency list from all enabled repositories:

```
dnf repograph
```

Output dependency list from rawhide repository:

```
dnf repograph --repoid rawhide
```

Output dependency list from rawhide and koji repository:

```
dnf repo-graph --repoid rawhide --repoid koji
```

## AUTHOR

See AUTHORS in your Core DNF Plugins distribution

## COPYRIGHT

2023, Red Hat, Licensed under GPLv2+

4.3.0

Mar 15, 2023

DNF-REPOGRAPH(8)