



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'fabs.3'***

#### ***\$ man fabs.3***

FABS(3)                   Linux Programmer's Manual                   FABS(3)

#### NAME

fabs, fabsf, fabsl - absolute value of floating-point number

#### SYNOPSIS

```
#include <math.h>
```

```
double fabs(double x);
```

```
float fabsf(float x);
```

```
long double fabsl(long double x);
```

Link with -lm.

Feature Test Macro Requirements for glibc (see feature\_test\_macros(7)):

fabsf(), fabsl():

```
_ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

```
|| /* Since glibc 2.19: */ _DEFAULT_SOURCE
```

```
|| /* Glibc versions <= 2.19: */ _BSD_SOURCE || _SVID_SOURCE
```

#### DESCRIPTION

These functions return the absolute value of the floating-point number

x.

#### RETURN VALUE

These functions return the absolute value of x.

If x is a NaN, a NaN is returned.

If x is -0, +0 is returned.

If x is negative infinity or positive infinity, positive infinity is returned.

#### ERRORS

No errors occur.

#### ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface            ? Attribute   ? Value   ?

??

?fabs(), fabsf(), fabsl() ? Thread safety ? MT-Safe ?

??

#### CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008.

The variant returning double also conforms to SVr4, 4.3BSD, C89.

#### SEE ALSO

abs(3), cabs(3), ceil(3), floor(3), labs(3), rint(3)

#### COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2017-09-15

FABS(3)