



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'fexecve.3'

\$ man fexecve.3

FEXECVE(3) Linux Programmer's Manual FEXECVE(3)

NAME

fexecve - execute program specified via file descriptor

SYNOPSIS

```
#include <unistd.h>
```

```
int fexecve(int fd, char *const argv[], char *const envp[]);
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

fexecve():

Since glibc 2.10:

```
_POSIX_C_SOURCE >= 200809L
```

Before glibc 2.10:

```
_GNU_SOURCE
```

DESCRIPTION

fexecve() performs the same task as execve(2), with the difference that the file to be executed is specified via a file descriptor, fd, rather than via a pathname. The file descriptor fd must be opened read-only (O_RDONLY) or with the O_PATH flag and the caller must have permission to execute the file that it refers to.

RETURN VALUE

A successful call to `fexecve()` never returns. On error, the function does return, with a result value of -1, and `errno` is set appropriately.

ERRORS

Errors are as for `execve(2)`, with the following additions:

`EINVAL` `fd` is not a valid file descriptor, or `argv` is `NULL`, or `envp` is `NULL`.

`ENOENT` The `close-on-exec` flag is set on `fd`, and `fd` refers to a script.

See `BUGS`.

`ENOSYS` The kernel does not provide the `execveat(2)` system call, and the `/proc` filesystem could not be accessed.

VERSIONS

`fexecve()` is implemented since `glibc 2.3.2`.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

??

?Interface ? Attribute ? Value ?

??

?`fexecve()` ? Thread safety ? MT-Safe ?

??

CONFORMING TO

`POSIX.1-2008`. This function is not specified in `POSIX.1-2001`, and is not widely available on other systems. It is specified in `POSIX.1-2008`.

NOTES

On Linux with `glibc` versions 2.26 and earlier, `fexecve()` is implemented using the `proc(5)` filesystem, so `/proc` needs to be mounted and available at the time of the call. Since `glibc 2.27`, if the underlying kernel supports the `execveat(2)` system call, then `fexecve()` is implemented using that system call, with the benefit that `/proc` does not need to be mounted.

The idea behind `fexecve()` is to allow the caller to verify (checksum)

the contents of an executable before executing it. Simply opening the file, checksumming the contents, and then doing an `execve(2)` would not suffice, since, between the two steps, the filename, or a directory prefix of the pathname, could have been exchanged (by, for example, modifying the target of a symbolic link). `fexecve()` does not mitigate the problem that the contents of a file could be changed between the checksumming and the call to `fexecve()`; for that, the solution is to ensure that the permissions on the file prevent it from being modified by malicious users.

The natural idiom when using `fexecve()` is to set the close-on-exec flag on `fd`, so that the file descriptor does not leak through to the program that is executed. This approach is natural for two reasons. First, it prevents file descriptors being consumed unnecessarily. (The executed program normally has no need of a file descriptor that refers to the program itself.) Second, if `fexecve()` is used recursively, employing the close-on-exec flag prevents the file descriptor exhaustion that would result from the fact that each step in the recursion would cause one more file descriptor to be passed to the new program. (But see BUGS.)

BUGS

If `fd` refers to a script (i.e., it is an executable text file that names a script interpreter with a first line that begins with the characters `#!`) and the close-on-exec flag has been set for `fd`, then `fexecve()` fails with the error `ENOENT`. This error occurs because, by the time the script interpreter is executed, `fd` has already been closed because of the close-on-exec flag. Thus, the close-on-exec flag can't be set on `fd` if it refers to a script, leading to the problems described in NOTES.

SEE ALSO

`execve(2)`, `execveat(2)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the

latest version of this page, can be found at

<https://www.kernel.org/doc/man-pages/>.

Linux

2019-10-10

FEXECVE(3)