



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'findfs.8'

\$ man findfs.8

FINDFS(8) System Administration FINDFS(8)

NAME

findfs - find a filesystem by label or UUID

SYNOPSIS

findfs NAME=value

DESCRIPTION

findfs will search the block devices in the system looking for a filesystem or partition with specified tag. The currently supported tags are:

LABEL=<label>

Specifies filesystem label.

UUID=<uuid>

Specifies filesystem UUID.

PARTUUID=<uuid>

Specifies partition UUID. This partition identifier is supported for example for GUID Partition Table (GPT) partition tables.

PARTLABEL=<label>

Specifies partition label (name). The partition labels are

supported for example for GUID Partition Table (GPT) or MAC
partition tables.

If the filesystem or partition is found, the device name will be
printed on stdout.

The complete overview about filesystems and partitions you can get for
example by

```
lsblk --fs
```

```
partx --show <disk>
```

```
blkid
```

EXIT STATUS

0

success

1

label or uuid cannot be found

2

usage error, wrong number of arguments or unknown option

ENVIRONMENT

LIBBLKID_DEBUG=all

enables libblkid debug output.

AUTHORS

findfs was originally written by Theodore Ts'o <tytso@mit.edu> and
re-written for the util-linux package by Karel Zak <kzak@redhat.com>.

SEE ALSO

blkid(8), lsblk(8), partx(8)

REPORTING BUGS

For bug reports, use the issue tracker at
<https://github.com/karelzak/util-linux/issues>.

AVAILABILITY

The findfs command is part of the util-linux package which can be
downloaded from Linux Kernel Archive
<<https://www.kernel.org/pub/linux/utils/util-linux/>>.